

Fisheries example integrating FLR

GMSE: an R package for generalised management strategy evaluation (Supporting Information 5)

A. Bradley Duthie^{1,3}, Jeremy J. Cusack¹, Isabel L. Jones¹, Jeroen Minderman¹, Erlend B. Nilsen², Rocío A. Pozo¹, O. Sarobidy Rakotonarivo¹, Bram Van Moorter², and Nils Bunnefeld¹

[1] Biological and Environmental Sciences, University of Stirling, Stirling, UK [2] Norwegian Institute for Nature Research, Trondheim, Norway [3] alexander.duthie@stir.ac.uk

Integration and simulation with fisheries

Early development of management strategy evaluation (MSE) models originated in fisheries (Polacheck et al., 1999; Smith et al., 1999; Sainsbury et al., 2000). Consequently, fisheries-focused software for MSE has been extensively developed, including R libraries that focus on the management of species of exceptional interest, such as the Atlantic Bluefin Tuna (*Thunnus thynnus*) (ABFTMSE; Carruthers and Butterworth, 2018a,b), and Indian Ocean Bigeye (*T. obesus*) and Yellowfin (*T. albacares*) Tuna (MSE-IO-BET-YFT; Kolody and Jumppanen, 2016). The largest of all such libraries is the Fisheries Library in R (FLR), which includes an extensive collection of tools targeted for fisheries science. The FLR library has been used in over a hundred publications (recent publications include Jardim et al., 2018; Mackinson et al., 2018; Utizi et al., 2018), and includes an MSE framework for evaluating different harvest control rules.

As part of the ConFooBio project, a central focus of GMSE is on simulating the management of animal populations of conservation interest, with a particular emphasis on understanding conservation conflict; further development of GMSE is expected to continue with this as a priority, further building upon the decision-making algorithms of managers and users to better understand how conflict arises and can be managed and mitigated. Hence, GMSE is not intended as a substitute for packages such as FLR, but the integration of these packages with GMSE could make use of GMSE's current and future simulation capabilities, and particularly the genetic algorithm. Such integration might be possible using the `gmse_apply` function, which allows for custom defined sub-models to be used within the GMSE framework, and with default GMSE sub-models. Hence, GMSE might be especially useful for modelling the management of fisheries under conditions of increasing competing stakeholder demands and conflicts. We do not attempt such an ambitious project here, but instead show how such a project could be developed through integration of FLR and `gmse_apply`.

Here we follow a Modelling Stock-Recruitment with FLSR example, then integrate this example with `gmse_apply` to explore the behaviour of a number of simulated fishers who are goal-driven to maximise their own harvest and a manager that aims to keep the fish stocks at a predefined target level. The core concept in GMSE is that manager can only incentivise fishers to harvest less or more by varying the cost of fishing (through e.g. taxes) given a set manager budget; please note that the manager cannot force the fisher to follow any policy. Based on the cost of fishing, the fisher can then given their own budget decide whether to invest in fishing or keep the budget. This concepts represents a nartural resource managment and conservation conflict, where one party aims to maximise their livelihood (fisher) and the other aims to keep a population at a sustainable level and prevent it from going extinct. Importantly, the manager does not have full control over fishers but can set policies to incentivise sustainable behaviour. We emphasise that this example is provided only as demonstration of how GMSE can potentially be integrated with already developed fisheries models, and is not intended to make recommendations for management in any population.

43 Integrating with the Fisheries Library in R (FLR)

44 The FLR toolset includes a series of packages, with several tutorials for using them. For simplicity, we
45 focus on a model of stock recruitment to be used as the population model in `gmse_apply`. This population
46 model will use sample data and one of the many available stock-recruitment models available in FLR, and a
47 custom function will be written to return a single value for stock recruitment. Currently, `gmse_apply` requires
48 that sub-models return subfunction results either as scalar values or data frames that are structured in the
49 same way as GMSE sub-models. But interpretation of scalar values is left up to the user (e.g., population
50 model results could be interpreted as abundance or biomass; manager policy could be interpreted as cost of
51 harvesting or as total allowable catch). For simplicity, the observation (i.e., estimation) model will be the
52 stock reported from the population model with error. The manager and user models, however, will employ
53 the full power of the default GMSE functions to simulate management and user actions. We first show how a
54 custom function can be made that applies the FLR toolset to a population model.

55 Modelling stock-recruitment for the population model

56 Here we closely follow a tutorial from the FLR project. To build the stock-recruitment model, the `FLCore`
57 package is needed (Kell et al., 2007). We also include the `ggplotFL` package for plotting.

```
install.packages("FLCore", repos="http://flr-project.org/R");  
install.packages("ggplotFL", repos="http://flr-project.org/R")
```

58 To start, we need to read in the `FLCore`, `ggplotFL` and `GMSE` libraries.

```
library(FLCore);
```

59 ## Loading required package: lattice

60 ## FLCore (Version 2.6.9, packaged: 2018-07-19 07:56:48 UTC)

```
library(ggplotFL);
```

61 ## Loading required package: ggplot2

62 ##

63 ## Attaching package: 'ggplot2'

64 ## The following object is masked from 'package:FLCore':

65 ##

66 ## %>%

67 ## Warning: replacing previous import 'ggplot2::%>%' by 'FLCore::%>%' when

68 ## loading 'ggplotFL'

```
library(GMSE);
```

69 For a simplified example in `GMSE`, we will simulate the process of stock recruitment over multiple time steps
70 using an example stock-recruitment model. The stock-recruitment model describes the relationship between
71 stock-recruitment and spawning stock biomass. The sample that we will work from is a recreation of the
72 North Sea Herring (`nsher`) dataset available in the `FLCore` package (Kell et al., 2007). This data set includes
73 recruitment and spawning stock biomass data between 1960 and 2004. First, we initialise an empty `FLSR`
74 object and read in the recreated herring data files from `GMSE`, which contains recruitment (`rec.n`) and
75 spawning stock biomass (`ssb.n`)

```
newFL <- FLSR(); # Initialises the empty FLSR object  
data(nsher_data); # Called from GMSE library (not from FLCore)
```

76 The recruitment (`rec.n`) and spawning stock biomass (`ssb.n`) data need to be in the form of a vector, array,
77 matrix to use them with `FLQuant`. We will convert `rec.n` and `ssb.n` into matrices.

```
rec.m      <- as.matrix(rec.n);  
ssb.m      <- as.matrix(ssb.n);
```

78 We can then construct two `FLQuant` objects, specifying the relevant years and units.

```
Frec.m     <- FLQuant(rec.m, dimnames=list(age=1, year = 1960:2004));  
Fssb.m     <- FLQuant(ssb.m, dimnames=list(age=1, year = 1960:2004));  
Frec.m@units <- "103";  
Fssb.m@units <- "t*103";
```

79 We then place the recruitment and spawning stock biomass data into the `FLSR` object that we created.

```
rec(newFL)  <- Frec.m;  
ssb(newFL)  <- Fssb.m;  
range(newFL) <- c(0, 1960, 0, 2004);
```

80 The `FLCore` package offers several stock-recruitment models. Here we use a Ricker model of stock recruitment
81 ([Ricker, 1954](#)), and insert this model into the `FLSR` object below.

```
model(newFL) <- ricker();
```

82 Parameters for the Ricker stock-recruitment model can be estimated with maximum likelihood.

```
newFL <- fmle(newFL);
```

83 Diagnostic plots, identical to those of the [modelling stock-recruitment tutorial](#) for the `nsher_ri` example, are
84 shown below in Figure 1. We note that these plots are made using the `FLCore` and `ggplotFL` packages, and
85 are not produced by, nor available in, the `GMSE` package.

```
plot(newFL, cex = 0.7);
```

86 We now have a working example of a stock-recruitment model, but for our integration with `gmse_apply`, we
87 will want a function that automates the above to simulate the process of updating the stock-recruitment
88 model. We do this using the custom function created below.

```
update_SR_model <- function(rec_m, ssb_m, years){  
  Frec_m      <- FLQuant(rec_m, dimnames=list(age = 1, year = years));  
  Fssb_m      <- FLQuant(ssb_m, dimnames=list(age = 1, year = years));  
  Frec_m@units <- "103";  
  Fssb_m@units <- "t*103";  
  rec(newFL)  <- Frec.m;  
  ssb(newFL)  <- Fssb.m;  
  range(newFL) <- c(0, years[1], 0, years[length(years)]);  
  model(newFL) <- ricker();  
  newFL       <- fmle(newFL);  
  return(newFL);  
}
```

89 The above function will be used within another custom function to predict the next time step of recruitment.

```
predict_recruitment <- function(rec_m, ssb_m, years, new_ssb){  
  newFL <- update_SR_model(rec_m, ssb_m, years);  
  a     <- params(newFL)[[1]] # Extract 'a' parameter of the Ricker model  
  b     <- params(newFL)[[2]] # Extract 'b' parameter of the Ricker model  
  rec   <- a * new_ssb * exp(-b * new_ssb); # Predict the new recruitment  
  return(rec)  
}
```




Figure 1: Output of the FLR plot function for an example Ricker model of stock recruitment on North Sea Herring data.

90 In `gmse_apply`, we will use the `predict_recruitment` function above as the resource (i.e., operational)
91 model. The `new_ssb` reads in the new spawning stock biomass, which will be calculated from the built-in
92 GMSE user model.

93 Integrating `predict_recruitment` with `gmse_apply`

94 The [FLR project](#) includes libraries that can be used to [perform a management strategy evaluation](#) (MSE)
95 under fisheries-focused observation, manager, and user models. We will not recreate [this approach](#), or
96 integrate any other sub-models into GMSE as was done for the population model above, although such
97 integration of sub-models should be possible using similar techniques. Our goal here is to instead show how
98 the `predict_recruitment` model created above can be integrated with `gmse_apply`, which can then make
99 use of the genetic algorithm to predict the fishers' behaviour.

100 We will use a custom observation model, which will simply estimate recruitment with some fixed error.

```
obs_ssb <- function(resource_vector){  
  obs_err <- rnorm(n = 1, mean = 0, sd = 100);  
  the_obs <- resource_vector + obs_err;  
  return(the_obs);  
}
```

101 Hence, we can now feed the data from `rec.m` and `ssb.m` through `predict_recruitment`, which will return a
102 value for new recruitment, and this new value can in turn be fed into `obs_ssb` to predict recruitment with
103 some error. We also need a new spawning stock biomass `new_ssb`, which we can just initialise with the
104 biomass from the last year in `ssb.m`

```
ssb_ini <- ssb.m[length(ssb.m)];  
new_rec <- predict_recruitment(rec_m = rec.m, ssb_m = ssb.m, years = 1960:2004,  
                              new_ssb = ssb_ini);  
obs_rec <- obs_ssb(new_rec);
```

105 An initial run of these models gives values of 3835.21 for `new_rec` and 3737.86 for `obs_rec`. We are now ready
106 to use the built-in manager and user sub-models in `gmse_apply`. We will assume that managers attempt to
107 keep a recruitment of 5000, and that there are 10 independent fishers who attempt to maximise their catch.
108 We assign a user budget of `manager_budget = 10000`, and all other values are set to GMSE defaults. In the
109 built-in GMSE functions, the manager will use the estimate of recruitment based on `obs_rec` and use it to
110 set the cost of harvesting (`culling` in GMSE).

```
yrspan <- 1960:2004;  
rec.m <- as.matrix(rec.n);  
ssb.m <- as.matrix(ssb.n);  
  
sim <- gmse_apply(res_mod = predict_recruitment, obs_mod = obs_ssb,  
                 rec_m = rec.m, ssb_m = ssb.m, years = yrspan,  
                 new_ssb = ssb_ini, manage_target = 5000, stakeholders = 10,  
                 manager_budget = 10000);  
print(sim);
```

```
111 ## $resource_results  
112 ## [1] 3835  
113 ##  
114 ## $observation_results  
115 ## [1] 3824.207  
116 ##  
117 ## $manager_results
```

```

118 ##           resource_type scaring culling castration feeding help_offspring
119 ## policy_1           1      NA      447           NA      NA      NA
120 ##
121 ## $user_results
122 ##           resource_type scaring culling castration feeding help_offspring
123 ## Manager           1      NA      0           NA      NA      NA
124 ## user_1             1      NA      2           NA      NA      NA
125 ## user_2             1      NA      2           NA      NA      NA
126 ## user_3             1      NA      2           NA      NA      NA
127 ## user_4             1      NA      2           NA      NA      NA
128 ## user_5             1      NA      2           NA      NA      NA
129 ## user_6             1      NA      2           NA      NA      NA
130 ## user_7             1      NA      2           NA      NA      NA
131 ## user_8             1      NA      2           NA      NA      NA
132 ## user_9             1      NA      2           NA      NA      NA
133 ## user_10            1      NA      2           NA      NA      NA
134 ##           tend_crops kill_crops
135 ## Manager           NA      NA
136 ## user_1             NA      NA
137 ## user_2             NA      NA
138 ## user_3             NA      NA
139 ## user_4             NA      NA
140 ## user_5             NA      NA
141 ## user_6             NA      NA
142 ## user_7             NA      NA
143 ## user_8             NA      NA
144 ## user_9             NA      NA
145 ## user_10            NA      NA

```

146 The resource and observation results above are interpreted in terms of recruitment, while the manager results
147 are interpreted in terms of the cost of harvesting a unit of spawning stock biomass and the user results are
148 interpreted in terms of how much biomass was harvested. Note in the run of `gmse_apply` that the arguments
149 for our custom resource and observation models (`predict_recruitment` and `obs_ssb`, respectively) are read
150 directly in as arguments of `gmse_apply` itself. The `gmse_apply` function will figure out which subfunctions
151 custom arguments should go to, then update these arguments as needed over the course of a single run of
152 `gmse_apply`.

153 Simulation with `gmse_apply` over multiple time steps

154 We are now ready to loop the `gmse_apply` function over multiple time steps. To do this, we will update the
155 `rec.m` and `ssb.m` matrices after each time step, simulating 20 years into the future. The population model
156 `predict_recruitment` will use these data to dynamically update parameters of the Ricker model, as might
157 occur in an empirical fishery that is being monitored. We will use the results from the observation model to
158 update recruitment for the new year in `rec.m`. For simplicity, spawning stock biomass prior to harvest will
159 be randomly sampled from a value in the last 10 years (i.e., from `ssb.m` between 1994 and 2004), but more
160 realistic models could relate this spawning stock biomass to recruitment and environmental variables from a
161 previous year; spawning stock biomass will be decreased after harvest based on user actions. The GMSE
162 initialisation and simulation is below.

```

# This code initialises the simulation -----
yrspan      <- 1960:2004;
rec.m       <- as.matrix(rec.n);
ssb.m       <- as.matrix(ssb.n);

```

```

ssb_ini      <- ssb.m[length(ssb.m)];
sim_old      <- gmse_apply(res_mod = predict_recruitment, obs_mod = obs_ssb,
                          rec_m = rec.m, ssb_m = ssb.m, years = yrspan,
                          new_ssb = ssb_ini, manage_target = 3500,
                          stakeholders = 10, manager_budget = 10000,
                          get_res = "Full");

# The code below simulates 20 time steps -----
sim_sum <- matrix(data = NA, nrow = 20, ncol = 6); # Hold results here
for(time_step in 1:20){
  # Update the relevant parameter values as necessary -----
  rand_ssb      <- sample(x = ssb.m[35:45], size = 1);
  harvest       <- sum(sim_old$basic_output$user_results[,3]);
  new_rec_m     <- c(sim_old$rec_m, sim_old$observation_vector);
  new_ssb_m     <- c(sim_old$ssb_m, rand_ssb - harvest);
  sim_old$rec_m <- matrix(data = new_rec_m, nrow = 1);
  sim_old$ssb_m <- matrix(data = new_ssb_m, nrow = 1);
  sim_old$years <- c(sim_old$years, time_step + 2004);
  sim_old$new_ssb <- sim_old$ssb_m[length(sim_old$ssb_m)];
  # Run a new simulation in the loop: custom functions are always specified -
  sim_new <- gmse_apply(get_res = "Full", old_list = sim_old,
                      res_mod = predict_recruitment, obs_mod = obs_ssb);
  # Record the results in sim_sum -----
  sim_sum[time_step, 1] <- time_step + 2004;
  sim_sum[time_step, 2] <- sim_new$basic_output$resource_results[1];
  sim_sum[time_step, 3] <- sim_new$basic_output$observation_results[1];
  sim_sum[time_step, 4] <- sim_new$basic_output$manager_results[3];
  sim_sum[time_step, 5] <- harvest;
  sim_sum[time_step, 6] <- sim_new$new_ssb;
  # Redefine the old list -----
  sim_old      <- sim_new;
}
colnames(sim_sum) <- c("Year", "Recruitment", "Recruit_estim", "Harvest_cost",
                    "Harvested", "SSB");
print(sim_sum);

```

	##	Year	Recruitment	Recruit_estim	Harvest_cost	Harvested	SSB
163	##						
164	##	[1,] 2005	4085	4177.6288	215	20	60.7603
165	##	[2,] 2006	4390	4455.6851	220	40	145.5799
166	##	[3,] 2007	3339	3361.3736	681	40	41.3340
167	##	[4,] 2008	4208	4242.1282	212	10	160.1926
168	##	[5,] 2009	1427	1457.4162	674	40	13.5966
169	##	[6,] 2010	3303	3352.0686	857	10	40.6133
170	##	[7,] 2011	4082	4201.3600	188	10	60.6639
171	##	[8,] 2012	2746	2786.3788	688	50	30.7603
172	##	[9,] 2013	3447	3532.5468	216	10	43.5966
173	##	[10,] 2014	3339	3267.0251	707	40	41.3340
174	##	[11,] 2015	4082	3904.3473	225	10	60.6639
175	##	[12,] 2016	633	640.6115	714	40	5.5913
176	##	[13,] 2017	4387	4510.4892	218	10	145.9025
177	##	[14,] 2018	1146	1113.4309	716	40	10.6133
178	##	[15,] 2019	4328	4273.1026	212	10	70.7603
179	##	[16,] 2020	4547	4545.8813	211	40	85.2627
180	##	[17,] 2021	4547	4566.8408	214	40	85.2627
181	##	[18,] 2022	4547	4451.9294	239	40	85.2627

182	## [19,] 2023	554	527.9121	713	40	4.8673
183	## [20,] 2024	4339	4375.7834	217	10	71.3340

184 The above output from `sim_sum` reports the recruitment (resource or operational model), recruitment estimate
 185 (observation error model), management set harvest cost (harvest control model), user harvested numbers
 186 (implementation model) and spawning stock biomass (SSB) simulation results. This example simulation
 187 demonstrates the ability of GMSE to integrate with fisheries libraries such as [FLR](#) through `gmse_apply`. In
 188 addition to being a useful wrapping function for MSE sub-models, `gmse_apply` can therefore be used to take
 189 advantage of the genetic algorithm in the GMSE default manager and user models. This flexibility will be
 190 retained in future versions of `gmse_apply`, allowing custom resource and observation models that are built for
 191 specific systems to be integrated with an increasingly complex genetic algorithm simulating various aspects
 192 of human decision-making.

193 Conclusions

194 GMSE is a general, flexible, tool for simulating the management of resources under situations of uncertainty
 195 and conflict. Management Strategy Evaluation ([Bunnefeld et al., 2011](#); [Punt et al., 2016](#)), the framework
 196 upon which GMSE is based, had its origin in fisheries management ([Polacheck et al., 1999](#); [Smith et al., 1999](#);
 197 [Sainsbury et al., 2000](#)), and here we showed one example of how GMSE could be integrated with the core
 198 package of the [Fisheries Library in R](#).

199 Future versions of GMSE will continue to be open-source and developed to avoid unnecessary dependencies
 200 (GMSE v.0.4.0.3 requires only base R). Key goals including (1) providing highly general and useful default
 201 `resource`, `observation`, `manager`, and `user` sub-models for a variety of MSE modelling tasks, (2) keeping
 202 these sub-models highly modular so that they can be developed in isolation given standardised data structures,
 203 and (3) allowing these modular sub-models to be integrated with custom defined sub-models as flexibly as
 204 possible using `gmse_apply`. Contributions in line with these goals, and suggestions for new features, can be
 205 made on [GitHub](#).

206 References

- 207 Bunnefeld, N., Hoshino, E., and Milner-Gulland, E. J. (2011). Management strategy evaluation: A powerful
 208 tool for conservation? *Trends in Ecology and Evolution*, 26(9):441–447.
- 209 Carruthers, T. and Butterworth, D. (2018a). ABT-MSE : An R package for atlantic bluefin tuna management
 210 strategy evaluation. *Collective Volume of Scientific Papers ICCAT*, 74(6):3553–3559.
- 211 Carruthers, T. and Butterworth, D. (2018b). Performance of example management procedures for atlantic
 212 bluefin tuna. *Collective Volume of Scientific Papers ICCAT*, 73(6):3542–3552.
- 213 Jardim, E., Eero, M., Silva, A., Ulrich, C., Pawlowski, L., Riveiro, I., Holmes, S. J., Ibaibarriaga, L., Alzorritz,
 214 N., Citores, L., Scott, F., Uriarte, A., Carrera, P., Duhamel, E., and Mosqueira, I. (2018). Testing spatial
 215 heterogeneity with stock assessment models. *PLoS One*, 13:e0190891.
- 216 Kell, L. T., Mosqueira, I., Grosjean, P., Fromentin, J.-M., Garcia, D., Hillary, R., Jardim, E., Mardle, S.,
 217 Pastoors, M. A., Poos, J. J., Scott, F., and Scott, R. D. (2007). FLR: an open-source framework for the
 218 evaluation and development of management strategies. *ICES Journal of Marine Science*, 64(4):640–646.
- 219 Kolody, D. and Jumpanan, P. (2016). IOTC Yellowfin and Bigeye Tuna Management Strategy Evaluation:
 220 Phase 1 Technical Support Project Final Report. Technical Report June, CSIRO: Oceans & Atmosphere.
- 221 Mackinson, S., Platts, M., Garcia, C., and Lynam, C. (2018). Evaluating the fishery and ecological
 222 consequences of the proposed North Sea multi-annual plan. *PLoS One*, 13:e0190015.

- 223 Polacheck, T., Klaer, N. L., Millar, C., and Preece, A. L. (1999). An initial evalutaion of management
224 strategies for the southern bluefin tuna fishery. *ICES Journal of Marine Science*, 56(6):811–826.
- 225 Punt, A. E., Butterworth, D. S., de Moor, C. L., De Oliveira, J. A. A., and Haddon, M. (2016). Management
226 strategy evaluation: Best practices. *Fish and Fisheries*, 17(2):303–334.
- 227 Ricker, W. E. (1954). Stock and recruitment. *Journal of the Fisheries Board of Canada*, 11(5):559–623.
- 228 Sainsbury, K. J., Punt, A. E., and Smith, A. D. (2000). Design of operational management strategies for
229 achieving fishery ecosystem objectives. *ICES Journal of Marine Science*, 57(3):731–741.
- 230 Smith, A. D. M., Sainsbury, K. J., and Stevens, R. A. (1999). Implementing effective fisheries-management
231 systems – management strategy evaluation and the Australian partnership approach. *ICES Journal of*
232 *Marine Science*, 56(6):967–979.
- 233 Utizi, K., Notti, E., Sala, A., Buzzi, A., Rodella, I., Simeoni, U., and Corbau, C. (2018). Impact assessment
234 of EMFF measures on Good Environmental Status (GES) as defined by Italy. *Marine Policy*, 88:248–260.