

The switchr package

Gabriel Becker

January 23, 2015

Reproducing results

- ▶ Use same version as original author(s)

Developing packages

- ▶ Program against latest/dev versions of dependencies

Collaboration

- ▶ Have single set of versions used by all participants

Github

Package repositories

SCM commit history

Install the versions we need

- ▶ on command
- ▶ directly from where they live

Distinct, side-by-side package libraries

- ▶ Don't want to clobber our main install to reproduce old result
- ▶ Development and analysis

Recreate others' environments

Publish our environments

- ▶ So that others can recreate them

Generalized Package repository

- ▶ List of packages
 - ▶ where their source lives
 - ▶ info necessary to retrieve them
- ▶ Optional version restrictions

Creating a new library

```
switchTo("mynewlib")
```

```
Switched to the 'mynewlib' computing environment. 29 packages  
To switch back to your previous environment type switchBack
```

Switching between libraries

```
switchBack()
```

```
Reverted to the 'mynewlib' computing environment. 29 packages
```

```
To switch back to your previous environment type switchBack()
```

```
switchTo("mynewlib")
```

```
Switched to the 'mynewlib' computing environment. 29 packages
```

```
To switch back to your previous environment type switchBack()
```

Creating a manifest

```
man = GithubManifest("gmbecker/fastdigest",  
"gmbecker/RCacheSuite", "duncantl/CodeDepends") man
```

A package manifest (PkgManifest object)

Contains 3 packages and 5 dependency repositories

Packages:

	name	type
1	fastdigest	git
2	RCacheSuite	git
3	CodeDepends	git

Installing from a manifest

```
install_packages("RCacheSuite", man)
head(installed.packages()[,c("Package", "Version")], 4)
```

	Package	Version
CodeDepends	"CodeDepends"	"0.3-5"
fastdigest	"fastdigest"	"0.5-1"
RCacheSuite	"RCacheSuite"	"0.0-1"
XML	"XML"	"3.98-1.1"

Generating a manifest from a library

```
man2 = libManifest() man2
```

A seeding manifest (SessionManifest object)

Describes a cohort of 4 package versions.

4 packages are listed in the underlying package manifest

Package versions:

	name	version
1	CodeDepends	0.3-5
2	fastdigest	0.5-1
3	RCacheSuite	0.0-1
4	XML	3.98-1.1

Publishing a manifest to a Gist

```
library(switchrGist) publishManifest(man, Gist())
```

Traveling back in time

```
man3.0 = rVersionManifest("3.0.0") man3.0
```

```
  "... "      "... "  
5006 "zmatrix"  "tarball"  
5007 "zoeppritz" "tarball"  
5008 "zoo"      "tarball"  
5009 "zooimage" "tarball"  
5010 "zyp"      "tarball"
```