

# Vegetation data access and taxonomic harmonization

## Version 0.5

Florian Jansen

March 21, 2012

### Abstract

An example session to show functionality and usage of R library `vegdata`.  
After installation of `vegdata` you can invoke this PDF with

```
> vignette('vegdata')
```

## 1 Preliminary notes

Some `vegdata` functions expect an installation, or more precisely the main directory structure, of the vegetation database program Turboveg for Windows (see '<http://www.synbiosys.alterra.nl/turboveg/>', and `?`). If the package can not find a Turboveg installation it will use the directory within the package installation path. If you want to use function `taxval` for taxonomic harmonization you will need to have GermanSL or an equally structured reference list. If you do not specify any, the most recent version of GermanSL will be used and if it can not be found within the specified path, it will be downloaded from <http://geobot.botanik.uni-greifswald.de/reflist>.

Turboveg uses dBase database format for storage. The package tries to deal with the limitations of that format but it is essential, that you use "Database -> Reindex" in Turboveg every time you delete something in your Turboveg database. Otherwise it will not be deleted immediately in the dBase file, instead it is only marked for deletion, i.e. it is still there when you access this file with R and will not be recognized as deleted until you reindex your Turboveg database.

## 2 Provided functionality

### 2.1 Database access

At the moment `vegdata` provides direct access to two different vegetation database formats:

**Turboveg** is a desktop program, written in VisualBasic. It provides basic functions to enter, import, maintain and export vegetation data. From the 2 000 000 vegetation plot registered in <http://www.GIVD.info> approximately 1.5 million are stored in Turboveg databases format.

**VegetWeb** is the German national vegetation database. VegetWeb is developed as a MySQL-Server database at the Federal Agency for Nature Conservation (BfN) and can be used via a PHP framework at <http://www.floraweb.de/vegetation/vegetweb/RechercheView.php>.

### 2.2 Taxonomic harmonisation

One of the most important steps in using vegetation data (from different sources) for statistical analysis is to take care about the taxonomic content of the names existing in the database. That is, to make sure, that exactly one (correct and valid) name defines one biological entity. Most researchers remember to convert synonyms to valid names but in many cases the care about e.g. monotypic subspecies or ambiguous taxonomic levels is lacking (?). The package offers the function `taxval` with different options for the adjustment of synonyms, monotypic taxa, taxonomic levels, members of aggregates and undetermined species.

## 2.3 Cover standardization

Turboveg provides different abundance codes and all kinds of user defined cover codes can easily be added. For vegetation analysis a unique species performance platform is needed which will in most cases be the percentage cover of the observed plot area. Therefore, for every abundance code class the mean cover percentage is defined in Turboveg. Since different scales can occur in a database and the storage format of the code table in Turboveg is somewhat strange, the function `tv.coverperc` provides automatic conversion for convenience.

## 2.4 Layer aggregation

The most frequently used sample unit in vegetation science is a plot based vegetation relevé (?). A Braun-Blanquet relevé is a sample of names and coverage (abundance) of species in a specified area (usually between 1 and 1000 m<sup>2</sup>) at a specific time. It contains (at least is intended to contain) a *complete* list of photo-autotrophic plants (or a defined subset) in that plot. This information can be stored in a three-column list of relevé ID, Taxon ID and performance measure (e.g. cover code).

Often additional information about the kind of occurrence is wanted. In Turboveg one additional column for the most widespread attribute is included by default: growth height classes. E.g. in a forest it is of interest, if a woody species reaches full height (tree layer) or occurs only as a small individual (herb layer). Other attributes like micro location (hummock or depression, rock or dead wood), development stage (juvenile or not, flowering status etc.) or the month of survey in a multi-seasonal survey could also be of interest and can be added in Turboveg. For analysis you may want to differentiate species with different species-plot attributes (e.g. growing in different layers). Function `tv.veg` provides possibilities for species-plot attribute handling.

## 2.5 Vegetation matrix

Turboveg stores relevés as a data frame of occurrences (s. below) but almost all functions and programs for vegetation analyses use plot-species cross-tables with a 0 value for non-occurrence = observed absence. Function `tv.veg` inflates the Turboveg list to matrix format with plots in rows and species in columns. Column names can be either species numbers, species letter-codes (default) or full names (with underscores instead of blanks to match the ).

# 3 Preparations

The best way to introduce the functionalities of the package is a session with example code.

We load the library as usual into our R environment.

```
> library(vegdata)
```

Many functions use the directory structure of Turboveg. The first time such a function is called, function `tv.home` tries to find your Turboveg installation path. Depending on whether you have Turboveg installed on your computer or not, it will give you a message about the Turboveg installation path or the path to the Turboveg directory structure of package `vegdata`.

```
> tv.home()
```

```
#####
Turboveg root directory is set to /home/florian/.wine/drive_c/Turbowin
If you want to change this use: options(tv_home="<path_to_your_Turbowin_root>")
#####
```

If you want to change this use:

```
> options(tv_home="path_to_your_Turboveg_root_directory")
```

## 4 Service functions

```
> tv.db()  
  
[1] "" "elbaue" "taxatest"
```

will give you a list of possible database names (directories within the Turboveg Data directory).

```
> tv.refl()
```

```
[1] "GermanSL 1.2"
```

GermanSL is the default Taxonomic reference list in package `vegdata`. Whenever you use a Turboveg database name in a function, the Reference list will be read from the database configuration file "tvwin.set", if possible.

Package `vegdata` contains several service functions to query the taxonomic information contained in the reference list.

```
> tax('Achillea millefolium')
```

```
Taxonomic evaluation list ( species.dbf ) of version GermanSL 1.2 not available.  
I will try to download the reference now.
```

SPECIES_NR	LETTERCODE	ABBREVIAT	
18	27	ACHI#MI Achillea millefolium agg.	
20	31	ACHIMIL Achillea millefolium	
21	32	ACHIM-M Achillea millefolium subsp. millefolium	
22	33	ACHIM-S Achillea millefolium subsp. sudetica	
8680	20096	ACHICOL Achillea millefolium subsp. collina	
8681	20097	ACHIPAN Achillea millefolium subsp. pannonica	
8682	20098	ACHIPAN Achillea millefolium var. lanata	
13221	26082	ACHIMIL Achillea millefolium var. firma	
26249	90019	ACHI*AB Achillea millefolium agg. x nobilis	
26250	90020	ACHIM*P Achillea millefolium x pannonica	
NATIVENAME SYNONYM VALID_NR			
18	Artengruppe Wiesen-Schafgarbe	FALSE	27
20	Gewöhnliche Wiesen-Schafgarbe	FALSE	31
21	Gewöhnliche Wiesen-Schafgarbe i.e.S.	FALSE	32
22	Sudeten-Wiesenschafgarbe	FALSE	33
8680	<NA>	TRUE	29
8681	<NA>	TRUE	34
8682	<NA>	TRUE	34
13221	<NA>	TRUE	31
26249	<NA>	TRUE	90028
26250	<NA>	FALSE	90020

"GermanSL 1.2" is not included in `vegdata` to keep the R package small. Instead the reference list will be automatically downloaded into the `tv_home` directory (see `tv.home()`), if it is not installed but needed. If you want to use a different list, specify `refl=<Name of your list>`. Function `tax` will use the given character string to look for all (partially) matching species names within the reference list

```
> tax('Achillea millefolium', strict=TRUE, verbose=TRUE)
```

SPECIES_NR	LETTERCODE	ABBREVIAT	AUTHOR	SYNONYM	VALID_NR	VALID_NAME						
20	31	ACHIMIL	Achillea millefolium	L.	FALSE	31	Achillea millefolium					
				NATIVENAME	RANG	GRUPPE	FAMILIE	AGG	AGG_NAME			
20	Gewöhnliche	Wiesen-Schafgarbe	SPE	S	Asteraceae	27	Achillea millefolium	agg.	SECUNDUM	HYBRID	BEGRUEND	EDITSTATUS
20	BfN(Wisskirchen u.	Haeupler 1998)	BfN(Wisskirchen u.	Haeupler 1998)	<NA>	<NA>	BfN					

Additional to the Turboveg standard fields comprehensive information for every taxon is stored in an extra file (tax.dbf). If you set option strict=TRUE, only the species with exact match to the given character string will be returned.

```
> tax('Elytrigia repens')$ABBREVIAT
```

```
[1] "Elytrigia repens subsp. arenosa" "Elytrigia repens"
[3] "Elytrigia repens var. caesia"     "Elytrigia repens var. littoralis"
[5] "Elytrigia repens var. repens"
```

```
> syn('Elytrigia repens')
```

Name swarm of *Elytrigia repens* :

SPECIES_NR	ABBREVIAT	SYNONYM	SECUNDUM
4078	6541 Agropyron repens subsp. caesium	TRUE BfN(Wisskirchen u. Haeupler 1998)	
4081	6544 Elymus repens subsp. repens s. l.	TRUE BfN(Wisskirchen u. Haeupler 1998)	
4791	10260 Elymus repens subsp. caesium	TRUE BfN(Wisskirchen u. Haeupler 1998)	
8714	20143 Agropyron caesium	TRUE BfN(Wisskirchen u. Haeupler 1998)	
8732	20167 Agropyron repens subsp. repens	TRUE BfN(Wisskirchen u. Haeupler 1998)	
9890	21639 Elytrigia repens	TRUE BfN(Wisskirchen u. Haeupler 1998)	
12065	24393 Triticum repens	TRUE BfN(Wisskirchen u. Haeupler 1998)	
13915	27778 Elymus repens	FALSE BfN(Wisskirchen u. Haeupler 1998)	
14007	27914 Agropyron repens	TRUE BfN(Wisskirchen u. Haeupler 1998)	
EDITSTATUS			
4078	BfN		
4081	Korrektur		
4791	BfN		
8714	BfN		
8732	BfN		
9890	BfN		
12065	BfN		
13915	BfN		
14007	BfN		

```
> childs(27, quiet=TRUE)$ABBREVIAT
```

```
[1] "Achillea collina"           "Achillea millefolium"
[3] "Achillea pannonica"        "Achillea roseoalba"
[5] "Achillea setacea"          "Achillea pratensis"
[7] "Achillea lanulosa"         "Achillea collina x millefolium"
[9] "Achillea collina x pannonica" "Achillea collina x pratensis"
[11] "Achillea collina x roseoalba" "Achillea collina x setacea"
[13] "Achillea millefolium x pannonica" "Achillea pratensis x roseoalba"
[15] "Achillea millefolium subsp. millefolium" "Achillea millefolium subsp. sudetica"
```

```
> parents('ACHIMIL')
```

SPECIES_NR	LETTERCODE	ABBREVIAT	AUTHOR	SYNONYM	VALID_NR
18	27 ACHI#MI	Achillea millefolium agg.	<NA>	FALSE	27
20643	60728 ACHI-SP	Achillea species	L.	FALSE	60728
20473	60463 ASTE-SP	Asteraceae species	Dumort.	FALSE	60463
20447	60415 ASTR-SP	Asterales species	Lindley	FALSE	60415
20326	60079 ASTI-SP	Asteridae species	Takht.	FALSE	60079
20320	60071 MAGL-SP	Magnoliopsida species	Dc.	FALSE	60071

20311	60049	MAGO-SP	Magnoliophytina species A. Braun & Doell	FALSE	60049
20285	60000	SPEA-SP	Spermatophyta species	<NA>	60000
29377	94419	"GEF-SP	"Gefaesspflanze" species	-	94419
10	0	"GRUETW	"Gruenliches etwas"	-	0
		VALID_NAME	NATIVE NAME	RANG	GRUPPE FAMILIE AGG
18	Achillea millefolium	agg.	Artengruppe Wiesen-Schaffgarbe	AGG	S Asteraceae 60728
20643	Achillea	species	Schaffgarbe	GAT	S Asteraceae 60463
20473	Asteraceae	species	<NA>	FAM	S <NA> 60415
20447	Asterales	species	<NA>	ORD	S <NA> 60079
20326	Asteridae	species	<NA>	UKL	S <NA> 60071
20320	Magnoliopsida	species	<NA>	KLA	S <NA> 60049
20311	Magnoliophytina	species	<NA>	UAB	S <NA> 60000
20285	Spermatophyta	species	<NA>	ABT	S <NA> 94419
29377	"Gefaesspflanze"	species	<NA>	AG2	G <NA> 0
10	"Gruenliches	etwas"	<NA>	ROOT	<NA> <NA> 0
		AGG_NAME	NACHWEIS		SECUNDUM
18	Achillea	species	BfN(Wisskirchen u. Haeupler 1998)	BfN(Wisskirchen u. Haeupler 1998)	
20643	Asteraceae	species	BfN(Wisskirchen u. Haeupler 1998)	BfN(Wisskirchen u. Haeupler 1998)	
20473	Asterales	species	Wisskirchen u. Haeupler 1998	Wisskirchen u. Haeupler 1998	
20447	Asteridae	species	Wisskirchen u. Haeupler 1998	Wisskirchen u. Haeupler 1998	
20326	Magnoliopsida	species	Wisskirchen u. Haeupler 1998	Wisskirchen u. Haeupler 1998	
20320	Magnoliophytina	species	Wisskirchen u. Haeupler 1998	Wisskirchen u. Haeupler 1998	
20311	Spermatophyta	species	Wisskirchen u. Haeupler 1998	Wisskirchen u. Haeupler 1998	
20285	"Gefaesspflanze"	species	Wisskirchen u. Haeupler 1998	Wisskirchen u. Haeupler 1998	
29377	"Gruenliches	etwas"	-	[ad-hoc-Taxon fÃ¼r GermanSL]	
10	"Gruenliches	etwas"	-	[ad-hoc-Taxon fÃ¼r GermanSL]	
	HYBRID		BEGRUEND EDITSTATUS GENERATION		
18	<NA>		<NA> BfN	1	
20643	<NA>		<NA> BfN	2	
20473	0	Abweichung zur Druckversion	Korrektur	3	
20447	0		<NA> BfN	4	
20326	0		<NA> BfN	5	
20320	0	Abweichung zur Druckversion	Korrektur	6	
20311	0	Abweichung zur Druckversion	Korrektur	7	
20285	0	Abweichung zur Druckversion	Korrektur	8	
29377	0		<NA> Ergaenzung	9	
10	0		<NA> Ergaenzung	10	

If you want to learn more about the taxonomic reference list for Germany, please look at ?. You can download the list manually from '<http://geobot.botanik.uni-greifswald.de/portal/reflist>'.

## 5 Taxonomic harmonisation

Care about the taxonomic content of the datasets is crucial for every analysis. Some of these steps can be automated with an appropriate taxonomic reference. For background and details see (?).

```
> db <- 'taxatest'
```

Defines the vegetation database name according to the name of the Turboveg database directory name

```
> tv.metainfo(db)
```

Metainformation, i.e. information about the kind of available information should always be given for every database. Since Turboveg does not ask and provide such information, write a simple text file called metainfo.txt and save it within the database folder. Turboveg does not provide any metadata handling. Database **taxatest** is an artificial dataset to show functionalities and necessary steps for taxonomic harmonization.

Let's have a look at the Turboveg data structure.

```

> obs.tax <- tv.obs(db)

reading observations ...

> # Adding species names
> species <- tax('all', syn=TRUE)
> obs.tax$name <- species$ABBREVIAT[match(obs.tax$SPECIES_NR, species$SPECIES_NR)]
> head(obs.tax[,1:4])

  RELEVE_NR SPECIES_NR COVER_CODE LAYER
1         2        27       2b     0
2         2       4685        4     1
3         2       4685        1     2
4         2       4685        1     6
5         1        31        3     6
6         1      20096       +     6

```

This condensed format shows only presences of species observations. Every species observation is stored in one row and the membership to a specific vegetation plot is given in column RELEVE\_NR.

## 5.1 Function taxval

We are using the taxonomic reference list GermanSL (?) which contains not only information about synonymy of species names, but also about the taxonomic hierarchy. This enables several semi-automatic enhancements of the taxonomic information stored in your vegetation database. If your database is not referenced to GermanSL (and can not be converted), you have to dismiss function **taxval** (option tax=FALSE in **tv. veg**) and do the taxonomic harmonization by hand (function **comb.species**).

```
> obs.taxval <- taxval(obs.tax, db=db, mono='lower')
```

Original number of names: 25

```
5 Synonyms found in dataset, adapted
SPECIES_NR          ABBREVIAT Freq.1 VALID_NR          VALID_NAME
20010   Cardamine pratensis subsp. pratensis    1    15133          Cardamine pratensis
20096   Achillea millefolium subsp. collina    1      29          Achillea collina
20583   Armeria maritima subsp. bottendorfensis 1    20585 Armeria maritima subsp. halleri
25203           Abies alpestris      2    4269          Picea abies
27309   Armeria bottendorfensis      1    20585 Armeria maritima subsp. halleri
```

Freq.2

0

0

0

0

0


1 monotypic taxa found in dataset, set to lower rank.

AGG_NR	AGG_NAME	AGG_RANG	MEMBER_NR	MEMB_NAME	MEMB_RANG	
66142	Acoraceae	species	FAM	61329	Acorus species	GAT

1 monotypic taxa found in dataset, set to lower rank.

AGG_NR	AGG_NAME	AGG_RANG	MEMBER_NR	MEMB_NAME	MEMB_RANG	
61329	Acorus	species	GAT	69	Acorus calamus	SPE

No taxa higher than ROOT found.



### 1. Field interpretation

- document your source(s) of taxonomic interpretation (Flora)
- specify determination certainty
- collect herbarium specimen

### 2. Database entry

- document field records / original literature
- reference as conservative as possible to a taxonomic reference list with all relevant taxa (synonyms, field aggregates, horticultural plants, ...)
- document your interpretations

### 3. Preparation for analyses

- convert synonyms
- summarize monotypic taxa
- clean up nested taxa
- clean up taxonomic ranks
- ...

## Three steps of taxonomic interpretation

- need of appropriate tools (software, reference lists)
- standards
- threefold attention

Figure 1: Steps of taxonomic interpretation

8 child taxa found in dataset, adapted

SPECIES_NR	ABBREVIAT	Freq.1	AGG	AGG_NAME	Freq.2
29	Achillea collina	1	27	Achillea millefolium agg.	1
31	Achillea millefolium	1	27	Achillea millefolium agg.	1
33	Achillea millefolium subsp. sudetica	1	31	Achillea millefolium	1
27	Achillea millefolium agg.	1	60728	Achillea species	1
2923	Hieracium pilosella	1	12273	Hieracium subg. Pilosella	1
15133	Cardamine pratensis	2	1105	Cardamine pratensis agg.	1
20945	Cardamine dentata	1	1105	Cardamine pratensis agg.	1
1105	Cardamine pratensis agg.	1	60845	Cardamine species	1

3 child taxa found in dataset, adapted

SPECIES_NR	ABBREVIAT	Freq.1	AGG	AGG_NAME	Freq.2
27	Achillea millefolium agg.	1	60728	Achillea species	1
31	Achillea millefolium	1	27	Achillea millefolium agg.	1
1105	Cardamine pratensis agg.	1	60845	Cardamine species	1

1 child taxa found in dataset, adapted

SPECIES_NR	ABBREVIAT	Freq.1	AGG	AGG_NAME	Freq.2
27	Achillea millefolium agg.	1	60728	Achillea species	1

Number of taxa after validation: 13

Warning: Critical Pseudonym(s) in dataset, please check  
to\_check check\_No check against SPECIES\_NR SECUNDUM  
Galium mollugo 2555 Galium mollugo auct. 27395 BfN(Wisskirchen u. Haeupler 1998)

Warning: Critical species in dataset, please check  
to\_check check\_No check against SPECIES\_NR SECUNDUM  
Dactylis glomerata 1843 Dactylis glomerata s. l. 26585 BfN(Wisskirchen u. Haeupler 1998)  
Galium mollugo 2555 Galium mollugo s. l. 26777 BfN(Wisskirchen u. Haeupler 1998)

The database contains 25 different names in the beginning.

**Synonyms** 5 of the species names are synonyms and are therefore transferred to legal taxon names, respectively numbers (see option syn='adapt'). If you want to preserve synonyms, choose option syn='conflict' or 'preserve'.

**Monotypic species within the area** Monotypic taxa are valid taxa which are the only child of their next higher taxonomic rank within the survey area. By default they will be converted by `taxval` to the higher rank. For instance *Poa trivialis* is in Germany only represented by *Poa trivialis subspecies trivialis*. Both taxa are valid, but for most analysis only one name for these identical entities must be used. By default a list of monotypic taxa within the GermanSL (whole Germany) is considered (see `tv.mono('GermanSL 1.2')`). The default is to set all monotypic species to the higher rank (because many monotypic subspecies can occur in vegetation databases).

If necessary, the procedure has to be repeated through the taxonomic

**Trimming the hierarchy** If your database contains the taxon *Asteraceae spec.*, the `taxval` code to follow would aggregate occurrences of all your Asteracea to the family level. To prevent this you can delete all observations above a certain taxonomic level. The default is not to trim the hierarchy (ROOT = "Greenish Something" is the toplevel).

**Solving the nestedness** If your database contains *Achillea millefolium* but also *Achillea millefolium agg.* for most analysis it will be necessary to coarsen the first (option ag='conflict') because *A. millefolium agg.* will probably include further occurrences of *Achillea millefolium*.

The procedure has to be repeated until all occurring taxonomical levels are considered. Especially with aggregates and their members the coarsening to the higher level can be a sad fate. If you have 100 occurrences of *Achillea millefolium* but a single one with *A. mill. agg.* you might want to clean your observational dataframe beforehand or do the aggregation afterwards manually with `tv.veg(db, ag='preserve')` and a manual correction with function `comb.species` (see below).

I confess that it is a strange and complete artificial example. Starting with 25 names in the beginning only 13 taxa survived the valuation. All others had to be converted.

```
> obs.taxval$Taxon <- species$ABBREVIAT[match(obs.taxval$SPECIES_NR, species$SPECIES_NR)]
> obs.taxval[order(obs.taxval$Name),c('Name','Taxon')]
```

	Name	Taxon
10	Abies alpestris	Picea abies
15	Abies alpestris	Picea abies
8	Acer pseudoplatanus	Acer pseudoplatanus
9	Acer pseudoplatanus	Acer pseudoplatanus
5	Achillea millefolium	Achillea species
1	Achillea millefolium agg.	Achillea species
6	Achillea millefolium subsp. collina	Achillea species
11	Achillea millefolium subsp. sudetica	Achillea species
7	Achillea species	Achillea species
16	Acoraceae species	Acorus calamus
19	Adonis aestivalis	Adonis aestivalis
20	Agrostis stolonifera var. palustris	Agrostis stolonifera var. palustris
22	Armeria bottendorfensis	Armeria maritima subsp. halleri
12	Armeria maritima subsp. bottendorfensis	Armeria maritima subsp. halleri
13	Armeria maritima subsp. elongata	Armeria maritima subsp. elongata
14	Armeria maritima subsp. halleri	Armeria maritima subsp. halleri
25	Cardamine dentata	Cardamine species
27	Cardamine pratensis	Cardamine species
26	Cardamine pratensis agg.	Cardamine species
28	Cardamine pratensis subsp. pratensis	Cardamine species
29	Cardamine species	Cardamine species
18	Dactylis glomerata	Dactylis glomerata
17	Galium mollugo	Galium mollugo
21	Hieracium pilosella	Hieracium subg. Pilosella
23	Hieracium subg. Pilosella	Hieracium subg. Pilosella
24	Picea abies	Picea abies
2	Quercus robur	Quercus robur
3	Quercus robur	Quercus robur
4	Quercus robur	Quercus robur

**Critical Pseudonyms** Taxon misapplication is maybe the greatest danger in using survey data. Known misapplications of names (.auct) are embedded in the GermanSL. Please pay attention, if these might also be relevant for your dataset.

Completely independent from the questions of correct taxonomic naming of a specific specimen, the boundary of a taxon interpretation can differ much ?. This should be adequately solved during data entry. Nevertheless these warnings gives you a last chance to rethink the correctness of your taxon assignments.

## 5.2 Coarsening to a specific taxonomic level

If you want only species in your analyses and no other taxonomic level use `taxval(obs, ag='adapt', rank='SPE')`. All hierarchical levels below the species level (including the above specified monotypic subspecies) are set to species level in this case.

```
> tmp <- taxval(obs.tax, refl='GermanSL 1.2', ag='adapt', rank='FAM')
> tmp$Taxon <- species$ABBREVIAT[match(tmp$SPECIES_NR, species$SPECIES_NR)]
```

```
> tmp[order(tmp$Taxon),c('Name','Taxon')]
```

	Name	Taxon
8	Acer pseudoplatanus	Aceraceae species
9	Acer pseudoplatanus	Aceraceae species
16	Acoraceae species	Acoraceae species
1	Achillea millefolium agg.	Asteraceae species
5	Achillea millefolium	Asteraceae species
6	Achillea millefolium subsp. collina	Asteraceae species
7	Achillea species	Asteraceae species
11	Achillea millefolium subsp. sudetica	Asteraceae species
21	Hieracium pilosella	Asteraceae species
23	Hieracium subg. Pilosella	Asteraceae species
25	Cardamine dentata	Brassicaceae species
26	Cardamine pratensis agg.	Brassicaceae species
27	Cardamine pratensis	Brassicaceae species
28	Cardamine pratensis subsp. pratensis	Brassicaceae species
29	Cardamine species	Brassicaceae species
2	Quercus robur	Fagaceae species
3	Quercus robur	Fagaceae species
4	Quercus robur	Fagaceae species
10	Abies alpestris	Pinaceae species
15	Abies alpestris	Pinaceae species
24	Picea abies	Pinaceae species
12	Armeria maritima subsp. bottendorfensis	Plumbaginaceae species
13	Armeria maritima subsp. elongata	Plumbaginaceae species
14	Armeria maritima subsp. halleri	Plumbaginaceae species
22	Armeria bottendorfensis	Plumbaginaceae species
18	Dactylis glomerata	Poaceae species
20	Agrostis stolonifera var. palustris	Poaceae species
19	Adonis aestivalis	Ranunculaceae species
17	Galium mollugo	Rubiaceae species

Check `?taxval` and `args(taxval)` for more options than the default.

### 5.3 Implementing other taxon views

If you wish to use another taxonomic concept than the default, you can use a conversion table to change synonymy etc. to catch your needs.

```
> newtaxa <- tv.taxval(obs, db, concept='korneck1996')
```

## 6 Vegetation matrices

At the moment there exists no formal class for vegetation data in R. But most functions in `vegan`, `ade4` or other packages expect vegetation data to be stored in a matrix with species in columns and plots in rows. Therefore, we need to inflate the Turboveg format (where zero occurrences are missing) to such a matrix.

`tv.veg` is a wrapper for the above mentioned functions and produces a vegetation matrix with relevés as rows and species as columns. Additionally care about species-plot attribute differentiation and combination, and the handling of species codes is provided.

### 6.1 Performance measures

At least in Europe most vegetation plots have some information about the cover of a species within the survey area, often given in some kind of alphanumeric code. Different codes systems can be combined by using the mean cover percentage per cover code class. Function `tv.coverperc` will do this job according to the definitions in *Turboveg/Popup/tvscale.dbf*.

```

> obs <- tv.obs(db)

reading observations ...

> obs <- tv.coverperc(db, obs)

Cover code used: Braun/Blanquet (old)
code      r      +      1      2      3      38      4      68      5      88
perc     1       2       3      13      38      68      88

Cover code used: Braun/Blanquet (new)
code      r      +      1      2m      2a      2b      3      38      4      68      5      88
perc     1       2       3       4       8       18      38      68      88

> head(obs)

  RELEVE_NR SPECIES_NR COVER_CODE LAYER DET_CERT SEASON MICROREL FLOWER COVERSCALE COVER_PERC
1          2        27      2b      0       0 Schlenke    0      02      18
2          2       4685      4      1       0 Schlenke    0      02      68
3          2       4685      1      2       1 Schlenke    0      02       3
4          2       4685      1      6       0       0 <NA>     10      02       3
5          1        31      3      6       0       0 <NA>      0      01      38
6          1      20096      +      6       0       0 Schlenke    1      01       2

```

If option `convcode = TRUE` (the default) the covercodes used in the Turboveg database (see file `tvscale.dbf`) are converted to (mean) percentage values according to the entries in the Turboveg Popup list "TVScale". For visual control the translated values will be printed on the screen.

A few simple possibilities for percentage cover transformations are included in function `tv.veg`, e.g. to use only presence-absence information you can choose option `cover.transform = 'pa'`.

## 6.2 Pseudospecies

How to account for different vegetation layers or other kinds of species differentiation?

The next step is the separation of pseudo-species. Pseudo-species are all kind of taxa split according to species-plot information beyond the performance measure which will be used within the matrix. At this point you have to decide which information should be preserved and which should be aggregated. For instance layer separation must be defined at this step. The default is to differentiate tree, shrub and herb layers but to combine finer layer specifications within them.

If we have more than one occurrence of the same species in a plot, e.g. because tree species growing as young stands and adult specimens were differentiated according to growth height classes, we have to create either pseudo-species which differentiate the occurrences in the resulting vegetation matrix or to combine species occurrences from different layers. For the latter we can use different calculations e.g. to sum up all cover percentages of different layers (`lc='sum'`) or the maximum value (`lc='max'`), mean value (`lc='mean'`). If we assume an independent occurrence of a species in different vertical layers, we can do the calculations with option `lc = 'layer'` (the default). This results in a probability sum: A species covering 50% in tree layer 1 and 50% in herb layer will get a combined cover of 75% because both layers will overlap 50% ( $1 - 0.5 \times 0.5$ ).

If you want to specify pseudo-species by other species-plot differentiation you can define a combination dataframe. Two example dataframes are included in the package (`lc.0` and `lc.1`). Option `comb` has to be given as a list with first element naming the column name holding the grouping variable and as second element the name of the combination dataframe. Try

```
> data(lc.0)
> tv.veg(db, pseudo = list(lc.0, c("LAYER")), lc = "layer")
```

and check the column names:

```
reading observations ...
Taxonomic reference list: GermanSL 1.2

converting cover code ...

Cover code used: Braun/Blanquet (old)
code      r      +      1      2      3      4      5
perc     1       2       3      13      38      68      88

Cover code used: Braun/Blanquet (new)
code      r      +      1      2m     2a     2b      3      4      5
perc     1       2       3       4       8       18      38      68      88
```

creating pseudo-species ...

combining occurrences using type LAYER and creating vegetation matrix ...

replacing species numbers with short names ...

```
[1] "AGRTS;P.6" "CARD#PR.6" "HIERSUG.6" "CARDPRA.6" "ACERPSE.5" "ACERPSE.6" "DACYGLO.6" "CARDPRA.6"
[9] "ACHICOL.6" "ARMEM-H"   "ARMEM-E"   "ARMEM-H"   "CARDDEN.6" "PICEABI.2" "PICEABI.3" "GALUMOL.6"
[17] "ACHI#MI"   "ARMEM-H.6" "HIERPIO"   "ACHIMIL.6" "ACHIM-S.6" "PICEABI.1" "QUERROB.1" "QUERROB.2"
[25] "QUERROB.6" "ACHI-SP.6" "CARD-SP.6" "ACOR-SP.6" "ADONAES.6"
```

Separated by dots and layer numbers you can see the preserved layers. For meaning of layer numbers see Turboveg Help.

Check cover aggregation for the default layer combination.

Beside layers you can use any kind of species-plot attributes to distinguish between occurrences, for instance in a multi-temporal survey.

```
> comb <- list(data.frame(SEASON=0:4, COMB=c(0,'Spring','Summer','Autumn','Winter')),'SEASON')
> tv.veg(db, tax=FALSE, pseudo=comb)
```

```
reading observations ...
Taxonomic reference list: GermanSL 1.2
```

converting cover code ...

```
Cover code used: Braun/Blanquet (old)
code      r      +      1      2      3      4      5
perc     1       2       3      13      38      68      88

Cover code used: Braun/Blanquet (new)
code      r      +      1      2m     2a     2b      3      4      5
perc     1       2       3       4       8       18      38      68      88
```

creating pseudo-species ...

combining occurrences using type LAYER and creating vegetation matrix ...

replacing species numbers with short names ...

```
AGRTS;P CARD#PR HIERSUG CARDPRA ACERPSE.Spring ACERPSE.Summer DACYGLO CARDPRA ACHICOL ARMEM-H
1       3       0       0       0           3           13      3       0       2       0
```

```

2      0      0      0      0      0      0      0      0      0      0      0      0
3      0      3      3      3      0      0      0      0      3      0      0      3
    ARMEM-E ARMEM-H CARDEN PICEABI GALUMOL ACHI#MI ARMEM-H HIERPIO ACHIMIL ACHIM-S PICEABI QUERROB
1      0      0      0      6      3      0      0      0      38     3      0      0
2      0      0      0      0      0      18     38     3      0      0      0      3      70
3      3      3      3      0      0      0      0      0      0      0      0      0      0
    ACHI-SP CARD-SP ACOR-SP ADONAES
1      3      0      0      3
2      0      0      0      0
3      0      3      3      0

```

```

> data(lc.1)
> veg <- tv.veg(db, lc = "sum", pseudo = list(lc.1, 'LAYER'), dec = 1, quiet=TRUE)

> veg[,1:10]

```

```

AGRTS;P HIERSUG ACERPSE ACERPSE.Shrub DACYGLO ARMEM-E ARMEM-H GALUMOL PICEABI.Tree QUERROB
1      3      0      3      13     3      0      0      3      6      0
2      0      3      0      0      0      0      38     0      3      3
3      0      3      0      0      0      3      6      0      0      0

```

### 6.3 Combine species by hand

Beside semi-automatic taxon harmonization with function `taxval` there are two possibilities to change Taxonomy manually. If you decide to interpret a certain species name in your database different than stored in the standard view of the taxonomic reference you can replace species numbers within the observational dataframe and run `taxval` later on.

```
> obs.tax$SPECIES_NR[obs.tax$SPECIES_NR == 27] <- 31
```

will replace all occurrences of *Achillea millefolium* agg. with *Achillea millefolium* which might be adequate for your survey and will prevent a too coarse taxon grouping. For a longer list of replacements you can use a data frame.

```
> taxon.repl <- data.frame(old=c(27), new=c(31))
> obs.tax$SPECIES_NR <- replace(obs.tax$SPECIES_NR, match(taxon.repl$old, obs.tax$SPECIES_NR), taxon.repl$new)
```

The second possibility is to use function `comb.species` on vegetation matrices.

```
> comb.species(veg, sel=c('QUERROB','QUERROB.Tree'))
```

```

The following names are combined to new name QUERROB
[1] "QUERROB"        "QUERROB.Tree"
AGRTS;P HIERSUG ACERPSE ACERPSE.Shrub DACYGLO ARMEM-E ARMEM-H GALUMOL PICEABI.Tree ACHI-SP
1      3      0      3      13     3      0      0      3      6      46
2      0      3      0      0      0      0      38     0      3      18
3      0      3      0      0      0      3      6      0      0      0
    CARD-SP ACOR-SP ADONAES QUERROB
1      0      0      3      0
2      0      0      0      74
3     15      3      0      0

```

will use the first name ('QUERROB') for the replacement column with the sum of the selected columns.

## 7 Site data

`tv.site` will load the site (header) data and does some basic corrections caused by Turboveg dBase format.

```
> site <- tv.site(db)
```

```
The following columns contain no data and are omitted
[1] REFERENCE  TABLE_NR   NR_IN_TAB  PROJECT    AUTHOR      SYNTAXON   UTM        ALTITUDE
[9] EXPOSITION MOSS_IDENT LICH_IDENT
```

```
The following numeric columns contain only 0 values and are omitted
[1] COV_TOTAL  COV TREES  COV SHRUBS COV HERBS  COV MOSSES COV LICHEN COV ALGAE  COV LITTER
[9] COV WATER  COV ROCK  TREE HIGH  TREE LOW   SHRUB HIGH SHRUB LOW  HERB HIGH  HERB LOW
[17] HERB MAX  CRYPT HIGH
```

```
The following numeric fields contain 0 values:
[1] INCLINATIO
```

```
Please check if these are really measured as 0 values or if they are not measured
and wrongly assigned because of Dbase restrictions.
```

If so, use something like:

```
site$Column_name[site$Column_name==0] <- NA
summary(site[,c('INCLINATIO')])
```

The function is quite straightforward. After loading the file `twhabita.dbf` from the specified database folder, warnings are given for plots without specified relevé area or date and fields are checked if they are empty (a lot of predefined header fields in Turboveg are often unused) or contain probably mistakable 0 values in numerical fields, due to dBase deficiencies (dBase can not handle NA = not available values reliably). It is stated in the output, if you have to check and possibly correct 0 values.

## 8 VegetWeb, the National German vegetation plot repository

I have written functions, which provide the possibility to access the data stored in VegetWeb, the German national vegetation database. VegetWeb is realised as MySQL database without API to access data directly. Therefore we need package RMySQL to make queries. Unfortunately there are no binary versions of RMySQL on CRAN any more. If you are working under Linux please install RMySQL with something like sudo apt-get install r-cran-rmysql. If you work with MS Windows you have to install RTools and the MySQL headers before you can compile RMySQL from source:

1. Install RTools from (<http://www.murdoch-sutherland.com/Rtools/>)
2. Install MySQL Connector C with installation option "full" from <http://dev.mysql.com/downloads/connector/c/> and copy the file libmysql.dll from the directory debug to the bin directory. Alternatively you can install a complete MySQL Server.
3. create a file Renviron.site in your R installation path in directory etc/ and add the correct path to your MySQL Connector installation e.g.:

```
MYSQL_HOME=C:/PROGRAMME/MySQL/MySQL Connector C 6.0.
```

4. open R and type  
`install.packages('RMySQL', type='source')`

If you run into trouble see <http://biostat.mc.vanderbilt.edu/wiki/Main/RMySQL>.

To prevent incompatibilities with Windows users who want to use Turboveg data but no VegetWeb data and who are not able or willing to install RMySQL, I excluded the VegetWeb functions from package vegdata, but they can be downloaded from the following website:

```

> library(RMySQL)
> source('http://geobot.botanik.uni-greifswald.de/download/r_package/vegetweb.r')

> vw.site()

No query string specified.
You can select vegetation plots from VegetWeb with queries like
  query="Projekt='T271'"
This will select all relevées from project T271, i.e Dengler 2007 Tuexenia.
If you want to see which selection parameters are available, try:
con <- vw.con()
dbListFields(con, "beobachtung")
summary(dbGetQuery(con, "SELECT pH FROM beobachtung"))
dbGetQuery(con, "SELECT * FROM projekt")
etc.

```

`vw.site` and `veg` are the user interface to retrieve data from VegetWeb respectively an open access mirror of the original BfN Server at the University of Greifswald (mirrored every Sunday).

```

> con <- vw.con()
> dbListTables(con)
> url.show("http://planto.de/OekoArt/ModellLog.php")

```

Gets names of VegetWeb tables and look for the Entity Relationship Diagram.

```

> con <- vw.con()
> dbListFields(con, "beobachtung")

```

[1] "Beobachtungs_ID"	"Beobachtungscode"	"Plotcode"
[4] "Vorbeobachtung"	"Projekt"	"DatumVon"
[7] "Datum"	"Moosidentifikation"	"Flechtenidentifikation"
[10] "Deckungsmethode"	"Deckungsmethode2"	"Nutzung"
[13] "Anteil Streuschicht"	"Anteil offene Wasserfläche"	"Anteil Fels"
[16] "Anteil Skelett"	"Anteil offener Boden"	"Deckung Baumschicht"
[19] "Deckung Strauchschnitt"	"Deckung Feldschicht"	"Deckung Kryptogamenschicht"
[22] "Deckung Schwimmblattschicht"	"Deckung Wasserpflanzenschicht"	"Höhe Baumschicht"
[25] "Höhe Strauchschnitt"	"Höhe Feldschicht"	"Höhe Kryptogamenschicht"
[28] "Tiefe Wasserpflanzen"	"Bemerkung"	"Erheber"
[31] "Digitalisierer"	"Zitat"	"Zittabellle"
[34] "Zitataufnahme"	"Verband"	"Assoziation"
[37] "Gesellschaftsbezeichnung"	"Subassoziation"	"Sukzessionsstatus"
[40] "Bestandsalter"	"Biozönotische Aspekte"	"Hydrologie"
[43] "Grundwasserflurabstand"	"Uferentfernung"	"Bodenart"
[46] "Bodentyp"	"Humusform"	"pH"
[49] "Phosphor"	"Kalium"	"Magnesium"
[52] "N-Gehalt"	"Biotoptyp"	"Pflegemaßnahmen"
[55] "Düngung"	"Schutz"	"Temperatur"
[58] "User"	"Modified"	

```
> dbGetQuery(con, "SELECT * FROM projekt")[1:2]
```

Projekt	Projektname
1 Bohn	Vegetationsaufnahmen bodensaurer Buchenwälder
2 BgWd	Bergwald - Datenbank
3 T252	Tüxenia 25 Becker

```

4   T251                               Tüxenia 25
5   T253                               Tüxenia 25 Bültmann
6   T262                               Tüxenia 26
7   T264                               Tüxenia 26
8   T254                               Tüxenia 25 Fuchs
9   T255                               Tüxenia 25 Gehlken
10  T269                               Tüxenia 26
11  T261                               Tüxenia 26
12  T268                               Tüxenia 26
13  T256                               Tüxenia 25 Otte und Maul
14  T265                               Tüxenia 26
15  T266                               Tüxenia 26
16  T282           Die Schwermetall-Vegetation des Harzes
17  T292   Populationsstruktur und Vergesellschaftung von Dictamnus albus L.
18  T275                               Tüxenia 27 Huntke
19  T274                               Tüxenia 27 Krämer u. Fartmann
20  T273                               Tüxenia 27 Brandes
21  T272                               Tüxenia 27 Klauck
22  T271                               Tüxenia 27 Dengler
23  T263                               Tüxenia 26
24  T276                               Tüxenia 27 Becker
25  T281           Die Allmendeweide "NSG Kanzelstein bei Eibach"
26  T291   Verbreitung, Vergesellschaftung und Ökologie von Lathraea squamaria
27  T293           Trittgesellschaften der nordrhein-westfälischen Dörfer
28  T294           Succession and management of calcareous dry grasslands
29  SYPF10      Synopsis der Pflanzengesellschaften Deutschlands
30  vNWR        Naturwaldreservate Bayerns
31  LANUV     LINFOS-Daten Landesamt für Natur, Umwelt und Verbraucherschutz NRW
32  T302       Tüxenia 30 Schmitt et al.

```

```
> query <- "Projekt='T302'"
```

Since several years all authors of **Tuemexenia** are committed to give their published data to VegetWeb. Therefore we can quite easily download the data from e.g.:  
Schmitt, Fartmann, Hoelzel 2010 Phytosociology and ecology of *Gladiolus palustris* in southern Bavaria, Tuexenia 30, p. 105-128.

```
> site <- vw.site(query)
> site.coord <- site[!is.na(site$"Geografische Breite"),]
```

## 9 Additional functions

Use `help(package='vegdata')` for a complete list of available functions and data sets in vegdata.

### 9.1 Combine different taxonomic reference lists

If you have to combine different taxonomic reference lists, functions `tv.compRef1` might be a starting point, comparing species numbers and/or species names of both lists.

```
> tv.compRef1('taxref1', 'taxref2')
```

### 9.2 Frequency tables

`syntab` produces a relative or absolute frequency table of a classified vegetation table with the possibility to filter according to threshold values. To exemplify the function we use the second dataset implemented in the package. It is the demonstration dataset from `?`, a selection of grassland relevés from the floodplains of the river Elbe.

```

> data(elbaue)

> clust <- vector('integer', nrow(elbaue.env))
> clust[elbaue.env$MGL < -50 & elbaue.env$SDGL < 50] <- 1           # dry sites, low deviation
> clust[elbaue.env$MGL < -50 & elbaue.env$SDGL >= 50] <- 2           # dry sites, high deviation
> clust[elbaue.env$MGL >= -50 & elbaue.env$SDGL >= 50] <- 3           # wet sites, high deviation
> clust[elbaue.env$MGL >= -50 & elbaue.env$SDGL < 50] <- 4           # wet sites, low deviation
> levels(clust) <- c('dry.ld','dry.hd', 'wet.hd','wet.ld')

```

We can e.g. look at the relative frequency of all species with more than 40% at least in one column, according to the height of the groundwater table (low or high) and the amplitude of the groundwater table fluctuations (high or low deviations from the mean).

```
> syntab(elbaue, clust, limit = 40)
```

	Number of clusters: 4			
	Cluster frequency 7 10 5 11			
	dry.ld	dry.hd	wet.hd	wet.ld
STELPAU	14	20	.	64
CAREVES	.	.	.	55
CAREPRA	43	70	.	.
CARDPRA	43	10	.	55
CIRSARV	43	.	.	9
DESCCES	57	.	.	18
AGRTPCAP	57	30	.	18
CAREACU	14	.	40	82
EUPHESU	43	.	.	.
GALUPAL	29	30	60	64
GALU#VE	71	20	.	.
POA TRI	14	30	20	45
GLYCMAX	.	.	80	45
ELYMREP	57	90	.	.
HOLCLAN	43	.	.	36
JUNUEFF	14	.	20	45
ALOPGEN	.	20	60	9
LATYPRA	43	.	.	9
ALOPPRA	71	90	20	36
PHALARU	14	40	80	64
POA PAL	29	60	20	45
POA #PR	57	60	20	27
ANTXODO	43	10	.	27
RANCFLA	.	.	.	55
RANCREP	29	60	40	73
RORIAMP	.	.	60	9
RUMEACE	43	.	.	27
RUMETHY	43	60	.	.
SIUMLAT	.	.	40	45
VICICRA	43	10	.	18
VICITET	57	10	.	.
TARA/AN	57	60	.	18

Or we can calculate the affiliation of species to abiotic clusters with the help of package `indicspecies`, which calculates species indicator values for one or several cluster (?).

```
> syntab(elbaue, clust, mupa=TRUE, fullnames=TRUE)
```

```
Number of clusters: 4
Cluster frequency 7 10 5 11
```

```
Taxonomic evaluation list ( species.dbf ) of version GermanSL 1.1 not available.
I will try to download the reference now.
```

	dry.ld	dry.hd	wet.hd	wet.ld	cl	stat	p.value
Cirsium arvense	43	.	.	9	1	0.64	0.009
Deschampsia cespitosa	57	.	.	18	1	0.72	0.011
Euphorbia esula	43	.	.	.	1	0.65	0.011
Galium verum agg.	71	20	.	.	1	0.83	0.002
Lathyrus pratensis	43	.	.	9	1	0.59	0.026
Vicia tetrasperma	57	10	.	.	1	0.71	0.006
Alopecurus geniculatus	.	20	60	9	3	0.65	0.026
Rorippa amphibia	.	.	60	9	3	0.77	0.006
Caltha palustris	.	.	.	36	4	0.60	0.050
Agrostis canina	.	.	.	36	4	0.60	0.045
Carex vesicaria	.	.	.	55	4	0.74	0.006
Carex gracilis	14	.	40	82	4	0.87	0.002
Ranunculus flammula	.	.	.	55	4	0.74	0.001
Carex praecox agg.	43	70	.	.	1+2	0.77	0.002
Agropyron repens subsp. caesium	57	90	.	.	1+2	0.87	0.001
Alopecurus pratensis	71	90	20	36	1+2	0.88	0.004
Rumex thyrsiflorus	43	60	.	.	1+2	0.73	0.017
Taraxacum officinale agg.	57	60	.	18	1+2	0.72	0.022
Cardamine nemorosa	43	10	.	55	1+4	0.69	0.036
Glyceria maxima	.	.	80	45	3+4	0.75	0.024
Sium latifolium	.	.	40	45	3+4	0.66	0.022

## 10 Vegetation analyses

The package *vegdata* serves mostly as a helper for the analysis of vegetation data. Several powerful R packages like *vegan* and others exist, to provide a very broad range of possibilities.

### 10.1 Plot coordinates of vegetation relevés into an interactive Google Map

If you do not have geodesic coordinates as used in Google Earth (EPSG-Code 4326), you can convert coordinates with R packages rgdal.

```
> library(rgdal)
> coord <- data.frame(HW=as.numeric(site.coord$Nordkoordinate), RW=as.numeric(site.coord$Ostkoordinate))
> coordinates(coord) <- c("RW", "HW")
> proj4string(coord) <- CRSargs(CRS("+init=epsg:31468")) # GK, 4. Stripe
> coord <- spTransform(coord, CRS("+init=epsg:4326")) # WGS 84, geographical coordinates, decimal degrees
> site.coord$long <- coordinates(coord)[,1]
> site.coord$lat <- coordinates(coord)[,2]
> site.coord$loc <- paste(site.coord$lat, site.coord$long, sep=':')
```

To give some information we will create Tips:

```
> site.coord$tip <- paste(paste('Releve_NR:', site.coord$RELEVE_NR), paste('Table:',site.coord$TABLE_NR), paste(
```

and the produced map will open in your standard web browser.

```
> places <- gvisMap(site.coord, 'loc', 'tip', options=list(showTip=TRUE, showLine=FALSE, enableScrollWheel=TRUE,
> plot(places)
```




Figure 2: Spatial distribution of vegetation plots from a VegetWeb project. The map is interactive and scalable.

## 10.2 Multivariate Ordinations

With the functions shown above we are now ready to do some example analyses in the wide area of vegetation analyses.

We can do, for instance, a “Nonmetric Multidimensional Scaling with Stable Solution from Random Starts Axis Scaling and Species Scores” which is a wrapper for Kruskal’s Non-metric Multidimensional Scaling (?) from Jari Oksanen (?).

```
> ## Data analyses
> library(vegan)
> veg.nmds <- metaMDS(elbaue, distance = "bray", trymax = 5, autotransform = FALSE, noshare = 1, expand = TRUE, t
```

To show the result in comparison with environmental measurements in a nice graphic we do some plotting magic.

```
> library(labdsrv)
> library(akima)
> color = function(x)rev(topo.colors(x))
> nmnds.plot <- function(ordi, site, var1, var2, disp, plottitle = 'NMDS', ...) {
+   lplot <- nrow(ordi$points);  lspc <- nrow(ordi$species)
+   filled.contour(interp(ordi$points[, 1], ordi$points[, 2], site[, var1]), ylim = c(-1, 1.1), xlim = c(-1.4, 1.
+   color.palette = color, xlab = var1, ylab = var2, main = plottitle,
+   key.title = title(main = var1, cex.main = 0.8, line = 1, xpd = NA),
+   plot.axes = { axis(1); axis(2)
+     points(ordi$points[, 1], ordi$points[, 2], xlab = "", ylab = "", cex= .5, col = 2, pch = '+')
+     points(ordi$species[, 1], ordi$species[, 2], xlab = "", ylab = "", cex=.2, pch = 19)
+     ordisurf(ordi, site[, var2], col = 'black', choices = c(1, 2), add = TRUE)
+     orditorp(ordi, display = disp, pch = " ")
+     legend("topright", paste("GAM of ", var2), col = 'black', lty = 1)
+   }
+ ,...)
+ }
```

The first axis of our NMDS plot show the influence of mean groundwater level on the patterns of the dataset. *Glyceria maxima* is marking the wet side of the gradient, whereas *Cnidium dubium* *Agrostis capillaris* or *Galium verum agg*, occur only at low mean groundwater level. The second axis can be assigned to the fluctuation of water levels measured as standard deviation of mean groundwater level. Species indicating high water fluctuation are *Agrostis stolonifera* or *Alopecurus geniculatus* whereas *Carex vesicaria* occurs only at more balanced situations.

```
> print(nmds.plot(veg.nmds, elbaue.env, disp='species', var1="MGL", var2="SDGL", plottitle = 'NMDS of Elbaue f')
```




Figure 3: Non-metric multidimensional scaling of the elbaue vegetation data with an overlay of mean ground-water table (colors) and standard deviation of groundwater level fluctuations (lines).