

Package ‘HVT’

May 8, 2024

Type Package

Date 2024-05-02

Title Constructing Hierarchical Voronoi Tessellations and Overlay
Heatmaps for Data Analysis

Version 24.5.1

Description Facilitates building topology preserving maps for rich multivariate data.
Credits to Mu Sigma for their continuous support throughout the development of the package.

License Apache License 2.0

Encoding UTF-8

Imports MASS, deldir, grDevices, splancs, conf.design, stats, dplyr,
purrr, magrittr, polyclip, ggplot2, tidyr, scales, cluster,
reshape2, data.table, ggforce, plyr, rlang, ganimate, gifski,
markovchain, methods

Depends R (>= 3.6.0)

BugReports <https://github.com/Mu-Sigma/HVT/issues>

URL <https://github.com/Mu-Sigma/HVT>

RoxygenNote 7.3.1

Suggests rmarkdown, testthat, geozoo, plotly, DT, patchwork, sp,
Hmisc, gridExtra, gtable, htmlwidgets, installr, skimr, tibble,
devtools, tidyverse, DataExplorer, htmltools,
corrplot, knitr, kableExtra

VignetteBuilder knitr

NeedsCompilation no

Author Zubin Dowlaty [aut],
Mu Sigma, Inc. [cre]

Maintainer ``Mu Sigma, Inc." <ird.experience@mu-sigma.com>

Repository CRAN

Date/Publication 2024-05-08 08:10:03 UTC

R topics documented:

displayTable	2
edaPlots	3
getTransitionProbability	4
plotAnimatedFlowmap	5
plotHVT	7
plotModelDiagnostics	9
plotNovelCells	10
plotQuantErrorHistogram	11
plotStateTransition	12
reconcileTransitionProbability	13
removeNovelty	14
scoreHVT	15
scoreLayeredHVT	17
trainHVT	19
Index	23

displayTable	<i>Table for displaying summary</i>
--------------	-------------------------------------

Description

This is the main function for displaying summary from model training and scoring

Usage

```
displayTable(
  data,
  columnName,
  value,
  tableType = "summary",
  scroll = TRUE,
  limit = 100
)
```

Arguments

data	List. A listed object from trainHVT or scoreHVT
columnName	Character. Name of the column that needs highlighting.
value	Numeric. The value above will be highlighted in red or green.
tableType	Character. Type of table to generate ('summary', 'compression')
scroll	Logical. A value to have a scroll or not in the table.
limit	Numeric. A value to indicate how many rows to display. Applicable for summary tableType.

Value

A consolidated table of results

Author(s)

Vishwavani <vishwavani@mu-sigma.com>

See Also

[trainHVT](#)

Examples

```
dataset <- data.frame(date = as.numeric(time(EuStockMarkets)),
                      DAX = EuStockMarkets[, "DAX"],
                      SMI = EuStockMarkets[, "SMI"],
                      CAC = EuStockMarkets[, "CAC"],
                      FTSE = EuStockMarkets[, "FTSE"])
hvt.results<- trainHVT(dataset,n_cells = 60, depth = 1, quant.err = 0.1,
                      distance_metric = "L1_Norm", error_metric = "max",
                      normalize = TRUE,quant_method = "kmeans")
displayTable(data = hvt.results[[3]]$compression_summary,
             columnName = 'percentOfCellsBelowQuantizationErrorThreshold',
             value = 0.8, tableType = "compression")

displayTable(data =hvt.results[[3]][['summary']], columnName= 'Quant.Error',
             value = 0.1, tableType = "summary")
```

edaPlots

plots for data analysis

Description

This is the main function that provides exploratory data analysis plots

Usage

```
edaPlots(df, time_series = FALSE, time_column)
```

Arguments

df	Dataframe. A data frame object.
time_series	Logical. A value to indicate whether the dataset is time_series or not.
time_column	Character. The name of the time column in the data frame.

Value

Five objects which include time series plots, data distribution plots, box plots, correlation plot and a descriptive statistics table.

Author(s)

Vishwavani <vishwavani@mu-sigma.com>

Examples

```
dataset <- data.frame(date = as.numeric(time(EuStockMarkets)),
                      DAX = EuStockMarkets[, "DAX"],
                      SMI = EuStockMarkets[, "SMI"],
                      CAC = EuStockMarkets[, "CAC"],
                      FTSE = EuStockMarkets[, "FTSE"])
edaPlots(dataset, time_series = TRUE, time_column = 'date')
```

getTransitionProbability

Creating Transition Probabilities list

Description

This is the main function to create transition probabilities list. The transition probability table quantifies the likelihood of transitioning from one state to another. States: The table includes the current states and the possible next states. Probabilities: For each current state, it lists the probability of transitioning to each of the next possible states.

Usage

```
getTransitionProbability(df, cellid_column, time_column)
```

Arguments

df	Data frame. The input data frame should contain two columns, cell ID from scoreHVT function and time stamp of that dataset.
cellid_column	Character. Name of the column containing cell IDs.
time_column	Character. Name of the column containing time stamps.

Value

Prints and stores a nested list of data frames with transition probabilities.

Author(s)

PonAnuReka Seenivasan <ponanureka.s@mu-sigma.com>

See Also

[trainHVT](#)
[scoreHVT](#)

Examples

```

dataset <- data.frame(date = as.numeric(time(EuStockMarkets)),
                     DAX = EuStockMarkets[, "DAX"],
                     SMI = EuStockMarkets[, "SMI"],
                     CAC = EuStockMarkets[, "CAC"],
                     FTSE = EuStockMarkets[, "FTSE"])
hvt.results<- trainHVT(dataset,n_cells = 60, depth = 1, quant.err = 0.1,
                      distance_metric = "L1_Norm", error_metric = "max",
                      normalize = TRUE,quant_method = "kmeans")
scoring <- scoreHVT(dataset, hvt.results)
cell_id <- scoring$scoredPredictedData$Cell.ID
time_stamp <- dataset$date
dataset <- data.frame(cell_id, time_stamp)
table <- getTransitionProbability(dataset, cellid_column = "cell_id",time_column = "time_stamp")

```

plotAnimatedFlowmap	<i>Generating flow maps and animations based on transition probabilities</i>
---------------------	--

Description

This is the main function for generating flow maps and animations based on transition probabilities including self states and excluding self states. Flow maps are a type of data visualization used to represent the transition probability of different states. Animations are the gifs used to represent the movement of data through the cells.

Usage

```

plotAnimatedFlowmap(
  hvt_model_output,
  transition_probability_df,
  df,
  animation = NULL,
  flow_map = NULL,
  fps_time = 1,
  fps_state = 1,
  time_duration = 2,
  state_duration = 2,
  cellid_column,
  time_column
)

```

Arguments

hvt_model_output
List. Output from a trainHVT function.

transition_probability_df
List. Output from getTransitionProbability function

<code>df</code>	Data frame. The input dataframe should contain two columns, cell ID from <code>scoreHVT</code> function and time stamp of that dataset.
<code>animation</code>	Character. Type of animation ('state_based', 'time_based', 'All' or NULL)
<code>flow_map</code>	Character. Type of flow map ('self_state', 'without_self_state', 'All' or NULL)
<code>fps_time</code>	Numeric. A numeric value for the frames per second of the time transition gif. (Must be a numeric value and a factor of 100). Default value is 1.
<code>fps_state</code>	Numeric. A numeric value for the frames per second of the state transition gif. (Must be a numeric value and a factor of 100). Default value is 1.
<code>time_duration</code>	Numeric. A numeric value for the duration of the time transition gif. Default value is 2.
<code>state_duration</code>	Numeric. A numeric value for the duration of the state transition gif. Default value is 2.
<code>cellid_column</code>	Character. Name of the column containing cell IDs.
<code>time_column</code>	Character. Name of the column containing time stamps

Value

A list of flow maps and animation gifs.

Author(s)

PonAnuReka Seenivasan <ponanureka.s@mu-sigma.com>, Vishwavani <vishwavani@mu-sigma.com>

See Also

[trainHVT](#)
[scoreHVT](#)
[getTransitionProbability](#)

Examples

```
dataset <- data.frame(date = as.numeric(time(EuStockMarkets)),
                     DAX = EuStockMarkets[, "DAX"],
                     SMI = EuStockMarkets[, "SMI"],
                     CAC = EuStockMarkets[, "CAC"],
                     FTSE = EuStockMarkets[, "FTSE"])

hvt.results<- trainHVT(dataset,n_cells = 60, depth = 1, quant.err = 0.1,
                      distance_metric = "L1_Norm", error_metric = "max",
                      normalize = TRUE,quant_method = "kmeans")

scoring <- scoreHVT(dataset, hvt.results)
cell_id <- scoring$scoredPredictedData$Cell.ID
time_stamp <- dataset$date
dataset <- data.frame(cell_id, time_stamp)

table <- getTransitionProbability(dataset, cellid_column = "cell_id",time_column = "time_stamp")
plots <- plotAnimatedFlowmap(hvt_model_output = hvt.results, transition_probability_df = table,
```

```
df = dataset, animation = 'All', flow_map = 'All', fps_time = 1, fps_state = 1, time_duration = 2,
state_duration = 2, cellid_column = "cell_id", time_column = "time_stamp")
```

plotHVT

Plot the hierarchical tessellations.

Description

This is the main plotting function to construct hierarchical voronoi tessellations in 1D, 2D or Interactive surface plot.

Usage

```
plotHVT(
  hvt.results,
  line.width = 0.5,
  color.vec = "black",
  pch1 = 21,
  centroid.size = 1.5,
  title = NULL,
  maxDepth = NULL,
  child.level,
  hmap.cols,
  quant.error.hmap = NULL,
  cell_id = FALSE,
  n_cells.hmap = NULL,
  label.size = 0.5,
  separation_width = 7,
  layer_opacity = c(0.5, 0.75, 0.99),
  dim_size = 1000,
  plot.type = "2Dhvt"
)
```

Arguments

<code>hvt.results</code>	(2DProj/2Dhvt/2Dheatmap/surface_plot) List. A list containing the output of <code>trainHVT</code> function which has the details of the tessellations to be plotted.
<code>line.width</code>	(2Dhvt/2Dheatmap) Numeric Vector. A vector indicating the line widths of the tessellation boundaries for each level.
<code>color.vec</code>	(2Dhvt/2Dheatmap) Vector. A vector indicating the colors of the boundaries of the tessellations at each level.
<code>pch1</code>	(2Dhvt/2Dheatmap) Numeric. Symbol of the centroids of the tessellations (parent levels). Default value is 21.
<code>centroid.size</code>	(2Dhvt/2Dheatmap) Numeric. Size of centroids of first level tessellations.
<code>title</code>	(2Dhvt) Character. Set a title for the plot. (default = NULL)

maxDepth	(2Dhvt) Numeric. An integer indicating the number of levels. (default = NULL)
child.level	(2Dheatmap/surface_plot) Numeric. Indicating the level for which the heat map is to be plotted.
hmap.cols	(2Dheatmap/surface_plot) Numeric or Character. The column number or column name from the dataset indicating the variables for which the heat map is to be plotted.
quant.error.hmap	(2Dheatmap) Numeric. A number indicating the quantization error threshold.
cell_id	(2Dhvt) Logical. To indicate whether the plot should have Cell IDs or not for the first layer. (default = FALSE)
n_cells.hmap	(2Dheatmap/surface_plot) Numeric. An integer indicating the number of cells/clusters per hierarchy (level)
label.size	(2Dheatmap) Numeric. The size by which the tessellation labels should be scaled. (default = 0.5)
separation_width	(surface_plot) Numeric. An integer indicating the width between two levels
layer_opacity	(surface_plot) Numeric. A vector indicating the opacity of each layer/ level
dim_size	(surface_plot) Numeric. An integer indicating the dimension size used to create the matrix for the plot
plot.type	Character. An option to indicate which type of plot should be generated. Accepted entries are '1D','2Dproj','2Dhvt','2Dheatmap'and 'surface_plot'. Default value is '2Dhvt'.

Value

plot object containing the visualizations of reduced dimension(1D/2D) for the given dataset.

Author(s)

Shubhra Prakash <shubhra.prakash@mu-sigma.com>, Sangeet Moy Das <sangeet.das@mu-sigma.com>

See Also

[trainHVT](#)

Examples

```
data("EuStockMarkets")
hvt.results <- trainHVT(EuStockMarkets, n_cells = 60, depth = 1, quant.err = 0.1,
                        distance_metric = "L1_Norm", error_metric = "max",
                        normalize = TRUE, quant_method="kmeans")

#change the 'plot.type' argument to '2Dproj' or '2DHVT' to visualize respective plots.
plotHVT(hvt.results, plot.type='1D')

#change the 'plot.type' argument to 'surface_plot' to visualize the Interactive surface plot
plotHVT(hvt.results, child.level = 1,
        hmap.cols = "DAX", plot.type = '2Dheatmap')
```

plotModelDiagnostics *Make the diagnostic plots for hierarchical voronoi tessellations*

Description

This is the main function that generates diagnostic plots for hierarchical voronoi tessellations models and scoring.

Usage

```
plotModelDiagnostics(model_obj)
```

Arguments

model_obj List. A list obtained from the trainHVT function or scoreHVT function

Value

For trainHVT, Minimum Intra-DataPoint Distance Plot, Minimum Intra-Centroid Distance Plot Mean Absolute Deviation Plot, Distribution of Number of Observations in Cells, for Training Data and Mean Absolute Deviation Plot for Validation Data are plotted. For scoreHVT Mean Absolute Deviation Plot for Training Data and Validation Data are plotted

Author(s)

Shubhra Prakash <shubhra.prakash@mu-sigma.com>

See Also

[plotHVT](#)

Examples

```
data("EuStockMarkets")
hvt.results <- trainHVT(EuStockMarkets, n_cells = 60, depth = 1, quant.err = 0.1,
                        distance_metric = "L1_Norm", error_metric = "max",
                        normalize = TRUE, quant_method="kmeans", diagnose = TRUE,
                        hvt_validation = TRUE)
plotModelDiagnostics(hvt.results)
```

plotNovelCells *Plot the identified outlier cell(s) in the voronoi tessellation map.*

Description

This is the main plotting function to construct hierarchical voronoi tessellations and highlight the outlier cells

Usage

```
plotNovelCells(
  plot.cells,
  hvt.map,
  line.width = c(0.6),
  color.vec = c("#141B41"),
  pch = 21,
  centroid.size = 0.5,
  title = NULL,
  maxDepth = 1
)
```

Arguments

plot.cells	Vector. A vector indicating the cells to be highlighted in the map
hvt.map	List. A list containing the output of trainHVT function which has the details of the tessellations to be plotted
line.width	Numeric Vector. A vector indicating the line widths of the tessellation boundaries for each level
color.vec	Vector. A vector indicating the colors of the boundaries of the tessellations at each level
pch	Numeric. Symbol of the centroids of the tessellations (parent levels) Default value is 21.
centroid.size	Numeric. Size of centroids of first level tessellations. Default value is 0.5
title	String. Set a title for the plot. (default = NULL)
maxDepth	Numeric. An integer indicating the number of levels. (default = NULL)

Value

Returns a ggplot object containing hierarchical voronoi tessellation plot highlighting the outlier cells

Author(s)

Shantanu Vaidya <shantanu.vaidya@mu-sigma.com>

See Also

[trainHVT](#)
[plotHVT](#)

Examples

```
data("EuStockMarkets")
hvt.results <- trainHVT(EuStockMarkets, n_cells = 60, depth = 1, quant.err = 0.1,
                        distance_metric = "L1_Norm", error_metric = "max",
                        normalize = TRUE, quant_method="kmeans")
#selected 55,58 are for demo purpose
plotNovelCells(c(55,58),hvt.results)
```

plotQuantErrorHistogram

Make the quantization error plots for training and scoring.

Description

This is the function that produces histograms displaying the distribution of Quantization Error (QE) values for both train and test datasets, highlighting mean values with dashed lines for quick evaluation.

Usage

```
plotQuantErrorHistogram(hvt.results, hvt.scoring)
```

Arguments

`hvt.results` List. A list of `hvt.results` obtained from the `trainHVT` function.
`hvt.scoring` List. A list of `hvt.scoring` obtained from the `scoreHVT` function.

Value

Returns the `ggplot` object containing the quantization error distribution plots for the given HVT results of training and scoring

Author(s)

Shubhra Prakash <shubhra.prakash@mu-sigma.com>

See Also

[plotHVT](#)

Examples

```

data("EuStockMarkets")
dataset <- data.frame(date = as.numeric(time(EuStockMarkets)),
                     DAX = EuStockMarkets[, "DAX"],
                     SMI = EuStockMarkets[, "SMI"],
                     CAC = EuStockMarkets[, "CAC"],
                     FTSE = EuStockMarkets[, "FTSE"])
rownames(EuStockMarkets) <- dataset$date
#Split in train and test
train <- EuStockMarkets[1:1302, ]
test <- EuStockMarkets[1303:1860, ]

hvt.results<- trainHVT(train,n_cells = 60, depth = 1, quant.err = 0.1,
                      distance_metric = "L1_Norm", error_metric = "max",
                      normalize = TRUE, quant_method = "kmeans")
scoring <- scoreHVT(test, hvt.results)
plotQuantErrorHistogram(hvt.results, scoring)

```

plotStateTransition *Creating State Transition Plot*

Description

This is the main function to create a state transition plot from a data frame. A state transition plot is a type of data visualization used to represent the changes or transitions in states over time for a given system. State refers to a particular condition or status of a cell at a specific point in time. Transition refers to the change of state for a cell from one condition to another over time.

Usage

```

plotStateTransition(
  df,
  sample_size = NULL,
  line_plot = NULL,
  cellid_column,
  time_column
)

```

Arguments

df	Data frame. The Input data frame should contain two columns. Cell ID from scoreHVT function and time stamp of that dataset.
sample_size	Numeric. An integer indicating the fraction of the data frame to visualize in the plot. Default value is 0.2
line_plot	Logical. A logical value indicating to create a line plot. Default value is NULL.
cellid_column	Character. Name of the column containing cell IDs.
time_column	Character. Name of the column containing time stamps.

Value

A plotly object representing the state transition plot for the given data frame.

Author(s)

PonAnuReka Seenivasan <ponanureka.s@mu-sigma.com>

See Also

[trainHVT](#)
[scoreHVT](#)

Examples

```
dataset <- data.frame(date = as.numeric(time(EuStockMarkets)),
  DAX = EuStockMarkets[, "DAX"],
  SMI = EuStockMarkets[, "SMI"],
  CAC = EuStockMarkets[, "CAC"],
  FTSE = EuStockMarkets[, "FTSE"])

hvt.results<- trainHVT(dataset,n_cells = 60, depth = 1, quant.err = 0.1,
  distance_metric = "L1_Norm", error_metric = "max",
  normalize = TRUE,quant_method = "kmeans")

scoring <- scoreHVT(dataset, hvt.results)
cell_id <- scoring$scoredPredictedData$Cell.ID
time_stamp <- dataset$date
dataset <- data.frame(cell_id, time_stamp)

plotStateTransition(dataset, sample_size = 1, cellid_column = "cell_id",time_column = "time_stamp")
```

reconcileTransitionProbability

Reconciliation of Transition Probability

Description

This is the main function for creating reconciliation plots and tables which helps in comparing the transition probabilities calculated manually and from markovchain function

Usage

```
reconcileTransitionProbability(
  df,
  hmap_type = NULL,
  cellid_column,
  time_column
)
```

Arguments

df	Data frame. The input data frame should contain two columns, cell ID from scoreHVT function and timestamp of that dataset.
hmap_type	Character. ('self_state', 'without_self_state', or 'All')
cellid_column	Character. Name of the column containing cell IDs.
time_column	Character. Name of the column containing timestamps

Value

A list of plotly heatmap objects and tables representing the transition probability heatmaps.

Author(s)

PonAnuReka Seenivasan <ponanureka.s@mu-sigma.com>, Vishwavani <vishwavani@mu-sigma.com>

See Also

[trainHVT](#)
[scoreHVT](#)

Examples

```
dataset <- data.frame(date = as.numeric(time(EuStockMarkets)),
                     DAX = EuStockMarkets[, "DAX"],
                     SMI = EuStockMarkets[, "SMI"],
                     CAC = EuStockMarkets[, "CAC"],
                     FTSE = EuStockMarkets[, "FTSE"])

hvt.results<- trainHVT(dataset,n_cells = 60, depth = 1, quant.err = 0.1,
                      distance_metric = "L1_Norm", error_metric = "max",
                      normalize = TRUE,quant_method = "kmeans")

scoring <- scoreHVT(dataset, hvt.results)
cell_id <- scoring$scoredPredictedData$Cell.ID
time_stamp <- dataset$date
dataset <- data.frame(cell_id, time_stamp)

reconcileTransitionProbability(dataset, hmap_type = "All",
                              cellid_column = "cell_id", time_column = "time_stamp")
```

removeNovelty

Remove identified novelty cell(s)

Description

This function is used to remove the identified novelty cells.

Usage

```
removeNovelty(outlier_cells, hvt_results)
```

Arguments

`outlier_cells` Vector. A vector with the cell number of the identified novelty

`hvt_results` List. A list having the results of the compressed map i.e. output of `trainHVT` function

Value

A list of two items

[[1]] Dataframe of novelty cell(s)

[[2]] Dataframe without the novelty cell(s) from the dataset used in model training

Author(s)

Shantanu Vaidya <shantanu.vaidya@mu-sigma.com>

See Also

[trainHVT](#)
[scoreLayeredHVT](#)

Examples

```
data("EuStockMarkets")
hvt.results <- trainHVT(EuStockMarkets, n_cells = 60, depth = 1, quant.err = 0.1,
                       distance_metric = "L1_Norm", error_metric = "max",
                       normalize = TRUE, quant_method="kmeans")
identified_Novelty_cells <- c(2, 10)
output_list <- removeNovelty(identified_Novelty_cells, hvt.results)
data_with_novelty <- output_list[[1]]
data_without_novelty <- output_list[[2]]
```

scoreHVT

Score which cell each point in the test dataset belongs to.

Description

This function scores each data point in the test dataset based on a trained hierarchical Voronoi tessellations model.

Usage

```
scoreHVT(
  data,
  hvt.results.model,
  child.level = 1,
  mad.threshold = 0.2,
  line.width = c(0.6, 0.4, 0.2),
  color.vec = c("navyblue", "slateblue", "lavender"),
  normalize = TRUE,
  seed = 300,
  distance_metric = "L1_Norm",
  error_metric = "max",
  yVar = NULL
)
```

Arguments

<code>data</code>	Data frame. A data frame containing the test dataset.
<code>hvt.results.model</code>	List. A list obtained from the trainHVT function
<code>child.level</code>	Numeric. A number indicating the depth for which the heat map is to be plotted.
<code>mad.threshold</code>	Numeric. A numeric value indicating the permissible Mean Absolute Deviation.
<code>line.width</code>	Vector. A vector indicating the line widths of the tessellation boundaries for each layer.
<code>color.vec</code>	Vector. A vector indicating the colors of the tessellation boundaries at each layer.
<code>normalize</code>	Logical. A logical value indicating if the dataset should be normalized. When set to TRUE, the data (testing dataset) is standardized by 'mean' and 'sd' of the training dataset referred from the trainHVT(). When set to FALSE, the data is used as such without any changes.
<code>seed</code>	Numeric. Random Seed to preserve the repeatability
<code>distance_metric</code>	Character. The distance metric can be L1_Norm(Manhattan) or L2_Norm(Euclidian). L1_Norm is selected by default. The distance metric is used to calculate the distance between an n dimensional point and centroid. The distance metric can be different from the one used during training.
<code>error_metric</code>	Character. The error metric can be mean or max. max is selected by default. max will return the max of m values and mean will take mean of m values where each value is a distance between a point and centroid of the cell.
<code>yVar</code>	Character. A character or a vector representing the name of the dependent variable(s)

Value

Dataframe containing scored data, plots and summary

Author(s)

Shubhra Prakash <shubhra.prakash@mu-sigma.com>, Sangeet Moy Das <sangeet.das@mu-sigma.com>

See Also

[trainHVT](#)
[plotHVT](#)

Examples

```
data("EuStockMarkets")
dataset <- data.frame(date = as.numeric(time(EuStockMarkets)),
                     DAX = EuStockMarkets[, "DAX"],
                     SMI = EuStockMarkets[, "SMI"],
                     CAC = EuStockMarkets[, "CAC"],
                     FTSE = EuStockMarkets[, "FTSE"])
rownames(EuStockMarkets) <- dataset$date
# Split in train and test
train <- EuStockMarkets[1:1302, ]
test <- EuStockMarkets[1303:1860, ]
#model training
hvt.results<- trainHVT(train,n_cells = 60, depth = 1, quant.err = 0.1,
                      distance_metric = "L1_Norm", error_metric = "max",
                      normalize = TRUE,quant_method = "kmeans")
scoring <- scoreHVT(test, hvt.results)
data_scored <- scoring$scoredPredictedData
```

scoreLayeredHVT	<i>Score which cell and what layer each data point in the test dataset belongs to</i>
-----------------	---

Description

This function that scores the cell and corresponding layer for each data point in a test dataset using three hierarchical vector quantization (HVT) models (Map A, Map B, Map C) and returns a data frame containing the scored layer output. The function incorporates the scored results from each map and merges them to provide a comprehensive result.

Usage

```
scoreLayeredHVT(
  data,
  hvt_mapA,
  hvt_mapB,
  hvt_mapC,
  mad.threshold = 0.2,
  normalize = TRUE,
  seed = 300,
```

```

distance_metric = "L1_Norm",
error_metric = "max",
child.level = 1,
yVar = NULL
)

```

Arguments

<code>data</code>	Data Frame. A data frame containing test dataset. The data frame should have all the variable(features) used for training.
<code>hvt_mapA</code>	A list of <code>hvt.results.model</code> obtained from <code>trainHVT</code> function while performing ‘ <code>trainHVT()</code> ’ on train data
<code>hvt_mapB</code>	A list of <code>hvt.results.model</code> obtained from <code>trainHVT</code> function while performing ‘ <code>trainHVT()</code> ’ on data with novelty(s)
<code>hvt_mapC</code>	A list of <code>hvt.results.model</code> obtained from <code>trainHVT</code> function while performing ‘ <code>trainHVT()</code> ’ on data without novelty(s)
<code>mad.threshold</code>	Numeric. A number indicating the permissible Mean Absolute Deviation
<code>normalize</code>	Logical. A logical value indicating if the dataset should be normalized. When set to <code>TRUE</code> , the data (testing dataset) is standardized by ‘ <code>mean</code> ’ and ‘ <code>sd</code> ’ of the training dataset referred from the <code>trainHVT()</code> . When set to <code>FALSE</code> , the data is used as such without any changes. (Default value is <code>TRUE</code>).
<code>seed</code>	Numeric. Random Seed.
<code>distance_metric</code>	Character. The distance metric can be <code>L1_Norm</code> (Manhattan) or <code>L2_Norm</code> (Euclidian). <code>L1_Norm</code> is selected by default. The distance metric is used to calculate the distance between an n dimensional point and centroid. The distance metric can be different from the one used during training.
<code>error_metric</code>	Character. The error metric can be <code>mean</code> or <code>max</code> . <code>max</code> is selected by default. <code>max</code> will return the max of m values and <code>mean</code> will take mean of m values where each value is a distance between a point and centroid of the cell.
<code>child.level</code>	Numeric. A number indicating the level for which the heat map is to be plotted.
<code>yVar</code>	Character. A character or a vector representing the name of the dependent variable(s)

Value

Dataframe containing scored layer output

Author(s)

Shubhra Prakash <shubhra.prakash@mu-sigma.com>, Sangeet Moy Das <sangeet.das@mu-sigma.com>, Shantanu Vaidya <shantanu.vaidya@mu-sigma.com>, Somya Shambhawi <somya.shambhawi@mu-sigma.com>

See Also

[trainHVT](#)
[plotHVT](#)

Examples

```

data("EuStockMarkets")
dataset <- data.frame(date = as.numeric(time(EuStockMarkets)),
                      DAX = EuStockMarkets[, "DAX"],
                      SMI = EuStockMarkets[, "SMI"],
                      CAC = EuStockMarkets[, "CAC"],
                      FTSE = EuStockMarkets[, "FTSE"])
rownames(EuStockMarkets) <- dataset$date

train <- EuStockMarkets[1:1302, ]
test <- EuStockMarkets[1303:1860, ]

###MAP-A
hvt_mapA <- trainHVT(train, n_cells = 150, depth = 1, quant.err = 0.1,
                    distance_metric = "L1_Norm", error_metric = "max",
                    normalize = TRUE, quant_method = "kmeans")

identified_Novelty_cells <- c(127,55,83,61,44,35,27,77)
output_list <- removeNovelty(identified_Novelty_cells, hvt_mapA)
data_with_novelty <- output_list[[1]]
data_with_novelty <- data_with_novelty[, -c(1,2)]

### MAP-B
hvt_mapB <- trainHVT(data_with_novelty, n_cells = 10, depth = 1, quant.err = 0.1,
                    distance_metric = "L1_Norm", error_metric = "max",
                    normalize = TRUE, quant_method = "kmeans")
data_without_novelty <- output_list[[2]]

### MAP-C
hvt_mapC <- trainHVT(data_without_novelty, n_cells = 135,
                    depth = 1, quant.err = 0.1, distance_metric = "L1_Norm",
                    error_metric = "max", quant_method = "kmeans",
                    normalize = TRUE)

###SCORE LAYERED
data_scored <- scoreLayeredHVT(test, hvt_mapA, hvt_mapB, hvt_mapC)

```

trainHVT

Constructing Hierarchical Voronoi Tessellations

Description

This is the main function to construct hierarchical voronoi tessellations. This is done using hierarchical vector quantization(hvq). The data is represented in 2D coordinates and the tessellations are plotted using these coordinates as centroids. For subsequent levels, transformation is performed on the 2D coordinates to get all the points within its parent tile. Tessellations are plotted using these transformed points as centroids.

Usage

```

trainHVT(
  dataset,
  min_compression_perc = NA,
  n_cells = NA,
  depth = 1,
  quant.err = 0.2,
  projection.scale = 10,
  normalize = FALSE,
  seed = 279,
  distance_metric = c("L1_Norm", "L2_Norm"),
  error_metric = c("mean", "max"),
  quant_method = c("kmeans", "kmedoids"),
  scale_summary = NA,
  diagnose = FALSE,
  hvt_validation = FALSE,
  train_validation_split_ratio = 0.8
)

```

Arguments

dataset	Data frame. A data frame, with numeric columns (features) will be used for training the model.
min_compression_perc	Numeric. An integer, indicating the minimum compression percentage to be achieved for the dataset. It indicates the desired level of reduction in dataset size compared to its original size.
n_cells	Numeric. An integer, indicating the number of cells per hierarchy (level).
depth	Numeric. An integer, indicating the number of levels. A depth of 1 means no hierarchy (single level), while higher values indicate multiple levels (hierarchy).
quant.err	Numeric. A number indicating the quantization error threshold. A cell will only breakdown into further cells if the quantization error of the cell is above the defined quantization error threshold.
projection.scale	Numeric. A number indicating the scale factor for the tessellations to visualize the sub-tessellations well enough. It helps in adjusting the visual representation of the hierarchy to make the sub-tessellations more visible.
normalize	Logical. A logical value indicating if the dataset should be normalized. When set to TRUE, scales the values of all features to have a mean of 0 and a standard deviation of 1 (Z-score).
seed	Numeric. A Random Numeric Seed to preserve the repeatability.
distance_metric	Character. The distance metric can be L1_Norm(Manhattan) or L2_Norm(Eucledian). L1_Norm is selected by default. The distance metric is used to calculate the distance between an n dimensional point and centroid.

error_metric	Character. The error metric can be mean or max. max is selected by default. max will return the max of m values and mean will take mean of m values where each value is a distance between a point and centroid of the cell.
quant_method	Character. The quantization method can be kmeans or kmedoids. Kmeans uses means (centroids) as cluster centers while Kmedoids uses actual data points (medoids) as cluster centers. kmeans is selected by default.
scale_summary	List. A list with user-defined mean and standard deviation values for all the features in the dataset. Pass the scale summary when normalize is set to FALSE.
diagnose	Logical. A logical value indicating whether user wants to perform diagnostics on the model. Default value is FALSE.
hvt_validation	Logical. A logical value indicating whether user wants to holdout a validation set and find mean absolute deviation of the validation points from the centroid. Default value is FALSE.
train_validation_split_ratio	Numeric. A numeric value indicating train validation split ratio. This argument is only used when hvt_validation has been set to TRUE. Default value for the argument is 0.8

Value

A Nested list that contains the hierarchical tessellation information. This list has to be given as input argument to plot the tessellations.

[[1]]	A list containing information related to plotting tessellations. This information will include coordinates, boundaries, and other details necessary for visualizing the tessellations
[[2]]	A list containing information related to Sammon's projection coordinates of the data points in the reduced-dimensional space.
[[3]]	A list containing detailed information about the hierarchical vector quantized data along with a summary section containing no of points, Quantization Error and the centroids for each cell.
[[4]]	A list that contains all the diagnostics information of the model when diagnose is set to TRUE. Otherwise NA.
[[5]]	A list that contains all the information required to generates a Mean Absolute Deviation (MAD) plot, if hvt_validation is set to TRUE. Otherwise NA
[[6]]	A list containing detailed information about the hierarchical vector quantized data along with a summary section containing no of points, Quantization Error and the centroids for each cell which is the output of 'hvq'
[[7]]	model info: A list that contains model-generated timestamp, input parameters passed to the model and the validation results

Author(s)

Shubhra Prakash <shubhra.prakash@mu-sigma.com>, Sangeet Moy Das <sangeet.das@mu-sigma.com>, Shantanu Vaidya <shantanu.vaidya@mu-sigma.com>

See Also[plotHVT](#)**Examples**

```
data("EuStockMarkets")
hvt.results <- trainHVT(EuStockMarkets, n_cells = 60, depth = 1, quant.err = 0.1,
  distance_metric = "L1_Norm", error_metric = "max",
  normalize = TRUE, quant_method="kmeans")
```

Index

- * **Diagnostics_or_Validation**
 - plotModelDiagnostics, 9
 - plotQuantErrorHistogram, 11
 - reconcileTransitionProbability, 13
- * **EDA**
 - displayTable, 2
 - edaPlots, 3
- * **Novelty_or_Outliers**
 - plotNovelCells, 10
 - removeNovelty, 14
- * **Scoring**
 - scoreHVT, 15
 - scoreLayeredHVT, 17
- * **Tessellation_and_Heatmap**
 - plotHVT, 7
- * **Training_or_Compression**
 - trainHVT, 19
- * **Transition_or_Prediction**
 - getTransitionProbability, 4
 - plotAnimatedFlowmap, 5
 - plotStateTransition, 12

displayTable, 2

edaPlots, 3

getTransitionProbability, 4, 6

plotAnimatedFlowmap, 5

plotHVT, 7, 9, 11, 17, 18, 22

plotModelDiagnostics, 9

plotNovelCells, 10

plotQuantErrorHistogram, 11

plotStateTransition, 12

reconcileTransitionProbability, 13

removeNovelty, 14

scoreHVT, 4, 6, 13, 14, 15

scoreLayeredHVT, 15, 17

trainHVT, 3, 4, 6, 8, 11, 13–15, 17, 18, 19